

Part Number : 1727040189

Series Number : 172704 Product Category : D-Sub Contacts Product Description : FCT High Power Contact, Male, Right-Angle, PCB Through Hole, 0.80µm Gold Mating Plating, 5.00µm Tin Termination Plating, 40.0A, 5.08mm Four Pronged Footprint Status : Active

Engineering Number : FMP012P104

Documents & Resources

Drawings

Drawing 1727040189_sd.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	@
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

General

Status	Active
Category	D-Sub Contacts
Series	172704
Description	FCT High Power Contact, Male, Right-Angle, PCB Through Hole, 0.80µm Gold Mating Plating, 5.00µm Tin Termination Plating, 40.0A, 5.08mm Four Pronged Footprint
Contact Type	High Power
Product Family	FCT D-Sub Connectors
Product Name	FCT Products
Туре	Mixed Layout
UPC	889056062657

Electrical

Current - Maximum per Contact	40.0A
-------------------------------	-------

Physical

Durability (mating cycles max)	500
Gender	Male
Material - Contact	Copper Alloy
Material - Plating Mating	Gold over Nickel
Material - Plating Termination	Tin over Nickel
Material - Retaining Clip	Copper Alloy
Net Weight	2.700/g
Orientation	Right-Angle
Packaging Type	Bag
Plating min - Mating	0.800µm
Plating min - Termination	5.000µm
Temperature Range - Operating	-55° to +155°C
Termination Style	Through Hole

Use with Part(s)

Description	Part Number
-------------	-------------

Application Tooling

Global

Description	Part Number
FCT Removal Tool for Size 8 Contacts	<u>1731121747</u>

This document was generated on Apr 13, 2024