

Part Number: 1731120081

Product Description: FCT High Power Contact, Male, Right-Angle, PCB Through Hole, 0.80μm Gold Mating Plating, 5.00μm Tin Termination Plating, 40.0A, 4.05mm PCB Drilling Diameter

Status: Active

Engineering Number: FMP009P104

Series Number: 173112

Product Category: D-Sub Contacts

Documents & Resources

Drawings

Drawing 1731120081_sd.pdf

Specifications

Packaging Specification 1731120008-PK-000.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | (8) |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | D-Sub Contacts |
| Series | 173112 |
| Description | FCT High Power Contact, Male, Right-Angle, PCB Through Hole, 0.80µm Gold Mating Plating, 5.00µm Tin Termination Plating, 40.0A, 4.05mm PCB Drilling Diameter |
| Contact Type | High Power |
| Product Family | FCT D-Sub Connectors |
| Product Name | FCT Products |
| Type | Mixed Layout |
| UPC | 889056324328 |

Electrical

| Current - Maximum per Contact | 40.0A |
|-------------------------------|-------|
|-------------------------------|-------|

Physical

| Durability (mating cycles max) | 500 |
|--------------------------------|------------------|
| Gender | Male |
| Material - Contact | Copper Alloy |
| Material - Plating Mating | Gold over Nickel |
| Material - Plating Termination | Tin over Nickel |
| Material - Retaining Clip | Copper Alloy |
| Net Weight | 2.800/g |
| Orientation | Right-Angle |
| Packaging Type | Bag |
| Plating min - Mating | 0.800µm |
| Plating min - Termination | 5.000µm |
| Temperature Range - Operating | -55° to +155°C |
| Termination Style | Through Hole |

Use with Part(s)

| Description | Part Number |
|-------------|-----------------------------|
| Use With | FCT Mixed Layout Connectors |

Application Tooling

Global

| Description | Part Number |
|---|-------------------|
| FCT Removal Tool for Size 8 Contacts | <u>1731121747</u> |

This document was generated on Apr 09, 2024