

Part Number: 1731120725

Product Description: FCT Machined Contact, Female, Crimp, 0.20µm Gold Plating, 20-24 AWG, 5000 Pieces

Status: Active

Series Number: 173112

**Product Category:** D-Sub Contacts

**Engineering Number:** FK20S-02V-6097

#### **Documents & Resources**

**Drawings** 

Drawing 1731120725\_sd.pdf

### **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>(3)</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### **EU RoHS Certificate of Compliance**

#### **Part Details**

#### General

Status	Active
Category	D-Sub Contacts
Series	173112
Description	FCT Machined Contact, Female, Crimp, 0.20µm Gold Plating, 20-24 AWG, 5000 Pieces
Contact Type	Machined Crimp
Product Family	FCT D-Sub Connectors
Product Name	FCT Products
Туре	Standard Density
UPC	191128856027

## Electrical

Current - Maximum per Contact	7.5A
-------------------------------	------

# Physical

Durability (mating cycles max)	200
Gender	Female
Material - Contact	Copper Alloy with Stainless Steel Sleeve
Material - Plating Mating	Gold over Nickel
Material - Plating Termination	Gold over Nickel
Net Weight	0.100/g
Orientation	Straight
Packaging Type	Bag
Plating min - Mating	0.200µm
Plating min - Termination	0.200µm
Temperature Range - Operating	-55° to +130°C
Termination Style	Crimp
Wire Size (AWG)	20, 22, 24

## Use with Part(s)

Description	Part Number
Use With	FCT Standard-Density Connectors

# **Application Tooling**

# Global

Description	Part Number
FCT Hand Crimp Tool, Mini Frame, 8-Step Adjust	<u>1731121730</u>
FCT Locator for Size 20 Contacts, Plug and Socket	<u>1731121733</u>
FCT Installation and Removal Tool for D-Subs	1731121744

This document was generated on Apr 09, 2024