

D-SUB M 3W3 FE TH



Image is for illustration purposes only. Please refer to product description.

Part number	09 69 200 0033
Specification	D-SUB M 3W3 FE TH
HARTING eCatalogue	https://b2b.harting.com/09692000033

Identification

Category	Connectors
Series	D-Sub
Identification	Mixed
Element	Connector
Description of the contact	Straight

Version

Gender	Female
Size	D-Sub 2
Number of contacts	3
Number of signal contacts	0
Number of special contacts	3
Locking type	Fixing flange with feed through hole Ø 3.1 mm
Details	Please order special contacts separately.

Technical characteristics

Insulation resistance	$> 5 \times 10^9 \Omega$
Limiting temperature	-55 ... +125 °C
Mating cycles	≥ 500
Test voltage $U_{r.m.s.}$	1 kV
Isolation group	IIIa ($175 \leq CTI < 400$)
Hot plugging	No



Pushing Performance
Since 1945

Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (Polyester) Shell: steel, tin plated
Colour (insert)	Green
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Requirement set with Hazard Levels	R26

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E102079
----------	-----------------------

Commercial data

Packaging size	100
Net weight	7.06 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140097346
ETIM	EC001136
eCl@ss	27440214 D-Sub coupler