


SERIES: PQDE6W-U | **DESCRIPTION:** DC-DC CONVERTER**FEATURES**


- high efficiency up to 88%
- single and dual output models available
- same side input/output connections
- 1,500 Vdc isolation
- industrial operating temp -40~85 °C
- wide 4:1 input range
- input under-voltage, output short-circuit, over-current, & over-voltage protections
- EN/BS EN 62368-1 certified



| MODEL | input voltage | | output voltage (Vdc) | output current | | output power max (W) | ripple & noise ¹ max (mVp-p) | efficiency ² typ (%) |
|-------------------------------|---------------|----------------|-------------------------|----------------|-------------|----------------------------|---|---------------------------------------|
| | typ (Vdc) | range (Vdc) | | min (mA) | max (mA) | | | |
| PQDE6W-Q24-D5-U ³ | 24 | 9~36 | ±5 | 0 | ±600 | 6 | 85 | 83 |
| PQDE6W-Q24-D12-U ³ | 24 | 9~36 | ±12 | 0 | ±250 | 6 | 85 | 87 |
| PQDE6W-Q24-D15-U ³ | 24 | 9~36 | ±15 | 0 | ±200 | 6 | 85 | 85 |
| PQDE6W-Q24-D24-U ³ | 24 | 9~36 | ±24 | 0 | ±125 | 6 | 85 | 87 |
| PQDE6W-Q24-S3-U ³ | 24 | 9~36 | 3.3 | 0 | 1500 | 4.95 | 85 | 77 |
| PQDE6W-Q24-S5-U ³ | 24 | 9~36 | 5 | 0 | 1200 | 6 | 85 | 83 |
| PQDE6W-Q24-S9-U ³ | 24 | 9~36 | 9 | 0 | 667 | 6 | 85 | 84 |
| PQDE6W-Q24-S12-U ³ | 24 | 9~36 | 12 | 0 | 500 | 6 | 85 | 85 |
| PQDE6W-Q24-S15-U ³ | 24 | 9~36 | 15 | 0 | 400 | 6 | 85 | 86 |
| PQDE6W-Q24-S24-U ³ | 24 | 9~36 | 24 | 0 | 250 | 6 | 85 | 86 |
| PQDE6W-Q48-D5-U | 48 | 18~75 | ±5 | 0 | ±600 | 6 | 85 | 83 |
| PQDE6W-Q48-D12-U | 48 | 18~75 | ±12 | 0 | ±250 | 6 | 85 | 87 |
| PQDE6W-Q48-D15-U | 48 | 18~75 | ±15 | 0 | ±200 | 6 | 85 | 88 |
| PQDE6W-Q48-S3-U | 48 | 18~75 | 3.3 | 0 | 1500 | 4.95 | 85 | 79 |
| PQDE6W-Q48-S5-U | 48 | 18~75 | 5 | 0 | 1200 | 6 | 85 | 83 |
| PQDE6W-Q48-S12-U | 48 | 18~75 | 12 | 0 | 500 | 6 | 85 | 87 |
| PQDE6W-Q48-S15-U | 48 | 18~75 | 15 | 0 | 400 | 6 | 85 | 88 |
| PQDE6W-Q48-S24-U | 48 | 18~75 | 24 | 0 | 250 | 6 | 85 | 88 |

- Notes:
1. From 5~100% load, nominal input, 20 MHz bandwidth oscilloscope. From 0~5% load, ripple and noise is <5% Vo.
 2. Measured at nominal input voltage and rated output load.
 3. Model is not CE certified.
 4. All specifications are measured at Ta=25°C, humidity < 75%, nominal input voltage, and rated output load unless otherwise specified.

PART NUMBER KEY



INPUT

| parameter | conditions/description | min | typ | max | units |
|-----------------------------------|--------------------------|------|-------|--------|-------|
| operating input voltage | 24 Vdc input models | 9 | 24 | 40 | Vdc |
| | 48 Vdc input models | 18 | 48 | 80 | Vdc |
| start-up voltage | 24 Vdc input models | | | 9 | Vdc |
| | 48 Vdc input models | | | 18 | Vdc |
| surge voltage | for maximum of 1 second | | | | |
| | 24 Vdc input models | -0.7 | | 50 | Vdc |
| | 48 Vdc input models | -0.7 | | 100 | Vdc |
| under voltage shutdown | 24 Vdc input models | 5.5 | 6.5 | | Vdc |
| | 48 Vdc input models | 12 | 15.5 | | Vdc |
| input current | 24 Vdc input models | | 268/5 | 275/12 | mA |
| | at nominal voltage | | 301/5 | 312/12 | mA |
| | 3.3 Vdc output | | | | |
| | 48 Vdc input models | | 130/4 | 134/8 | mA |
| | at nominal input voltage | | 150/4 | 155/8 | mA |
| | 3.3 Vdc output | | | | |
| reflected ripple current | at nominal input voltage | | 20 | | mA |
| filter | Pi filter | | | | |
| input reverse polarity protection | no | | | | |
| no load power consumption | | | 0.12 | | W |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|--------------------------------------|---|-----|------|-------|-------|
| maximum capacitive load ¹ | 3.3 Vdc output models | | | 1,800 | μF |
| | 5 Vdc output models | | | 1,000 | μF |
| | 9 Vdc output models | | | 680 | μF |
| | 12, ±5 Vdc output models | | | 470 | μF |
| | 15 Vdc output models | | | 220 | μF |
| | all other models | | | 100 | μF |
| total regulation ² | 0% to full load | | ±1 | ±3 | % |
| line regulation | from low line to high line, full load | | | | |
| | positive outputs | | ±0.2 | ±0.5 | % |
| | negative outputs | | ±0.5 | ±1 | % |
| load regulation ³ | from 5% to full load | | | | |
| | positive outputs | | ±0.5 | ±1 | % |
| | negative outputs | | ±0.5 | ±1.5 | % |
| cross regulation | dual output models: main output 50% load secondary output from 10~100% load | | | ±5 | % |
| switching frequency ⁴ | PWM mode | | 300 | | kHz |

OUTPUT (CONTINUED)

| parameter | conditions/description | min | typ | max | units |
|------------------------------|---|-----|-----|-------|-------|
| transient response deviation | 25% load step change, nominal input voltage | | ±5 | ±8 | % |
| | 3.3, 5, ±5 Vdc output models | | ±3 | ±5 | % |
| transient recovery time | 25% load step change, nominal input voltage | | 300 | 500 | µs |
| temperature coefficient | at full load | | | ±0.03 | %/°C |

Note:

1. The specified maximum capacitive load value for positive and negative output is identical.
2. Output voltage accuracy of ±5 & ±9 Vdc output converter for 0~5% load is ±5% max.
3. At 0~100% load, the max load regulation is ±5%.
4. Value is based on full load. At loads <50%, the switching frequency decreases with decreasing load.

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------|---------------------------|-----|-----|-----|-------|
| over voltage protection | | 110 | | 160 | % |
| over current protection | | 110 | 140 | 190 | % |
| short circuit protection | continuous, self recovery | | | | |

SAFETY AND COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|------------------------------|--|-----------|-------|-----|-------|
| isolation voltage | input to output for 1 minute at 1 mA max | 1,500 | | | Vdc |
| isolation resistance | input to output at 500 Vdc | 1,000 | | | MΩ |
| isolation capacitance | input to output, 100 kHz / 0.1 V | | 1,000 | | pF |
| safety approvals | certified to 62368: EN/BS EN | | | | |
| conducted emissions | CISPR32/EN55032 Class A (w/o external components), Class B (see Fig. 3-2 for recommended circuit) EN50121-3-2 150kHz-500kHz 99dBuV (see Fig. 3-2 for recommended circuit) EN55016-2-1 500kHz-30MHz 93dBuV (see Fig. 3-2 for recommended circuit) | | | | |
| radiated emissions | CISPR32/EN55032 Class A (w/o external components), Class B (see Fig. 3-1 for recommended circuit) EN50121-3-2 30MHz-230MHz 40dBuV/m at 10m, 230MHz-1GHz 47dBuV/m at 10m (see Fig. 3-1 for recommended circuit) | | | | |
| ESD | IEC/EN61000-4-2 Contact ±4kV, perf. Criteria B EN50121-3-2 Contact ±6kV/Air ±8kV, perf. Criteria A | | | | |
| radiated immunity | IEC/EN61000-4-3 10V/m, perf. Criteria A EN50121-3-2 20V/m, perf. Criteria A | | | | |
| EFT/burst | IEC/EN61000-4-4 ±2kV (See Fig. 3-1 for recommended circuit), perf. Criteria B EN50121-3-2 ±2kV 5/50ns 5kHz (See Fig. 3-1 for recommended circuit), perf. Criteria A | | | | |
| surge | IEC/EN61000-4-5 line to line ±2KV (see Fig. 3-1 for recommended circuit), perf. Criteria A EN50121-3-2 line to line ±1KV (see Fig. 3-1 for recommended circuit), perf. Criteria A | | | | |
| conducted immunity | IEC/EN61000-4-6 3 Vr.m.s, perf. Criteria A EN50121-3-2 10 Vr.m.s, perf. Criteria A | | | | |
| voltage dips & interruptions | IEC/EN61000-4-29, 0%-70%, perf. Criteria B | | | | |
| MTBF | as per MIL-HDBK-217F, 25°C | 1,000,000 | | | hours |
| RoHS | yes | | | | |

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|-----------------------------------|-----|-----|-----|-------|
| operating temperature | see derating curve | -40 | | 85 | °C |
| storage temperature | | -55 | | 125 | °C |
| storage humidity | non-condensing | 5 | | 95 | % |
| vibration | IEC/EN61373 - Category 1, Grade B | | 10 | | G |

SOLDERABILITY

| parameter | conditions/description | min | typ | max | units |
|--------------------------------------|---------------------------------|-----|-----|-----|-------|
| pin soldering resistance temperature | 1.5 mm from case for 10 seconds | | | 300 | °C |


MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|---------------|--|-----|------|-----|-------|
| dimensions | 55.00 x 52.30 x 19.00 [2.165 x 2.059 x 0.748 inch] | | | | mm |
| case material | aluminum alloy | | | | |
| weight | | | 43.5 | | g |

MECHANICAL DRAWING


units: mm [inch]
 wire range: 24-12 AWG
 tightening torque: Max 0.4 N·m
 tolerance: ±1.00[±0.039]

| PIN CONNECTIONS | | |
|-----------------|----------|------|
| PIN | Function | |
| | Single | Dual |
| 1 | GND | GND |
| 2 | Vin | Vin |
| 3 | NC | NC |
| 4 | Case | Case |
| 5 | NC | NC |
| 6 | +Vo | +Vo |
| 7 | NC | 0V |
| 8 | 0V | -Vo |




DERATING CURVE

TEMPERATURE DERATING CURVE




EFFICIENCY CURVES


EFFICIENCY VS INPUT VOLTAGE (full load)




EFFICIENCY VS OUTPUT LOAD (Vin = 24 Vdc)



EFFICIENCY VS INPUT VOLTAGE (full load)



EFFICIENCY VS OUTPUT LOAD (Vin = 24 Vdc)



APPLICATION CIRCUIT

This series has been tested according to the following recommended circuits (Figures 1 & 2) before leaving the factory. If you want to further reduce the input and output ripple, you can increase the input and output capacitors or select capacitors of low equivalent impedance provided that the capacitance is less than the maximum capacitive load of the model.

Figure 1
Single Output Models




Figure 2
Dual Output Models




Table 1

| Vin (Vdc) | Cin (μF/V) | Cout (μF/V) |
|-----------|-----------------------|-------------|
| 24 | 100 μF/50 V | 10 μF/50 V |
| 48 | 10 μF ~ 47 μF / 100 V | 10 μF/50 V |

EMC RECOMMENDED CIRCUIT

Figure 3




Table 2

| Recommended External Circuit Components | | |
|---|--|----------------|
| Vin (Vdc) | 24 | 48 |
| FUSE | choose according to actual input current | |
| MOV | S20K30 | S14K60 |
| C0 | 680 μF / 50 V | 680 μF / 100 V |
| C1 | 1 μF / 50 V | 1 μF / 100 V |
| C2 | 330 μF / 50 V | 330 μF / 50 V |
| C3 | 4.7 μF / 50 V | 4.7 μF / 100 V |
| C4 | refer to the Cout in Fig. 1 & 2 | |
| LCM | 4.7 mH | |
| CY1, CY2 | 1 nF / 2 kV | |

Notes: For EMC tests part ① in Figure 3 was used for immunity and part ② for emissions test. Selecting based on needs.

REVISION HISTORY

| rev. | description | date |
|------|-----------------|------------|
| 1.0 | initial release | 11/07/2022 |

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC

a bel group

Headquarters

20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.