

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mini feed-through terminal block, nom. voltage: 250 V, nominal current: 24 A, number of connections: 2, connection method: Screw connection, 1 level, Rated cross section: 2.5 mm², cross section: 0.2 mm² - 2.5 mm², mounting type: NS 15, color: gray

Your advantages

- Separating disks, partition plates, and test sockets complete the range of accessories
- Space saving thanks to compact design and mounting option on a 15 mm DIN rail
- Clear arrangement thanks to marking of all terminal points
- Easy potential distribution thanks to standardized plug-in bridges

Commercial data

Item number	1414006
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE12
Product key	BE1261
Catalog page	Page 516 (CL1-2011)
GTIN	4017918021269
Weight per piece (including packing)	4.25 g
Weight per piece (excluding packing)	3.906 g
Customs tariff number	85369010
Country of origin	IN

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Technical data

Product properties

Product type	Miniature terminal block
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	4 kV
Maximum power dissipation for nominal condition	0.77 W

Connection data

Number of connections per level	2
Nominal cross section	2.5 mm ²

1 level

Screw thread	M3
Tightening torque	0.6 ... 0.8 Nm
Stripping length	7 mm
Internal cylindrical gage	A3
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.2 mm ² ... 2.5 mm ²
Cross section AWG	24 ... 14 (converted acc. to IEC)
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section, flexible [AWG]	24 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm ² ... 2.5 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	2.5 mm ²
Cross-section with insertion bridge, rigid	2.5 mm ²
Cross-section with insertion bridge, flexible	2.5 mm ²
2 conductors with same cross section, solid	0.2 mm ² ... 0.75 mm ²
2 conductors with same cross section, flexible	0.2 mm ² ... 0.75 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm ² ... 0.75 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 1.5 mm ²
Nominal current	24 A
Maximum load current	24 A (with a 2.5 mm ² conductor cross section)
Nominal voltage	250 V
Nominal cross section	2.5 mm ²

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Ex data

Rated data (ATEX/IECEx)

Identification	Ex e II
Operating temperature range	-50 °C ... 110 °C
Ex-certified accessories	1414035 D-MBK 2,5/E
	1413227 ATP-MBK
	1205053 SZS 0,6X3,5
	1421633 E/MK
List of bridges	Fixed bridge / FBRN 10-5-EX / 3000612
Bridge data	20 A / 2.5 mm ²
List of bridges	Insertion bridge / EB 2- 5 / 1401158
	Insertion bridge / EB 3- 5 / 1401145
	Insertion bridge / EB 10- 5 / 1401132
Bridge data	19 A / 2.5 mm ²
Ex temperature increase	34 K (22 A / 2,5 mm ²)
Rated voltage	176 V
at bridging with insertion bridge	176 V
for bridging with bridge	176 V
Rated insulation voltage	160 V
output	(Permanent)

Ex level General

Rated current	22 A
Maximum load current	22 A
Contact resistance	0.35 mΩ

Ex connection data General

Torque range	0.6 Nm ... 0.8 Nm
Nominal cross section	2.5 mm ²
Rated cross section AWG	14
Connection capacity rigid	0.2 mm ² ... 2.5 mm ²
Connection capacity AWG	24 ... 14
Connection capacity flexible	0.2 mm ² ... 2.5 mm ²
Connection capacity AWG	24 ... 14
2 conductors with same cross section, solid	0.2 mm ² ... 0.75 mm ²
2 conductors with the same cross-section AWG rigid	24 ... 18
2 conductors with same cross section, stranded	0.2 mm ² ... 0.75 mm ²
2 conductors with the same cross-section AWG flexible	24 ... 18

Dimensions

Width	5.2 mm
End cover width	1 mm

Material specifications

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Color	gray
Flammability rating according to UL 94	V2
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-40 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Electrical tests

Surge voltage test

Test voltage setpoint	4.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 2.5 mm ²	0.3 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.5 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 15
Test force setpoint	1 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.2 mm ² / 0.2 kg
	2.5 mm ² / 0.7 kg
Result	Test passed

Environmental and real-life conditions

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 15
---------------	-------

MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



Drawings

Circuit diagram



MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1414006>

 CSA Approval ID: 13631				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	300 V	20 A	28 - 12	-

 cULus Recognized Approval ID: E60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B				
	300 V	20 A	30 - 12	-
Use group C				
	300 V	20 A	30 - 12	-

 ATEX Approval ID: KEMA 03ATEX2380U				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	176 V	22 A	-	0.2 - 2.5

 EAC Ex Approval ID: RU C-DE.HA91.B.00066				
--	--	--	--	--

 IECEx Approval ID: IECEx KEM 07.0016U				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	176 V	22 A	-	0.2 - 2.5

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 8.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

Accessories



Note: Applying some accessories below might limit this product.

FBRNI 2-5 N - Fixed bridge

3000175

<https://www.phoenixcontact.com/us/products/3000175>




Fixed bridge, pitch: 5 mm, number of positions: 2, color: silver

FBRNI 3-5 N - Fixed bridge

3000162

<https://www.phoenixcontact.com/us/products/3000162>



Fixed bridge, pitch: 5 mm, number of positions: 3, color: silver

MBK 2,5/E - Mini feed-through terminal block

1414006


<https://www.phoenixcontact.com/us/products/1414006>



FBRNI 4-5 N - Fixed bridge

3000159

<https://www.phoenixcontact.com/us/products/3000159>




Fixed bridge, pitch: 5 mm, number of positions: 4, color: silver

FBRNI 10-5 N - Fixed bridge

2770639

<https://www.phoenixcontact.com/us/products/2770639>



Fixed bridge, pitch: 5.2 mm, number of positions: 10, color: silver

 Max. current carrying capacity: 24 A

MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



FBRNI 20-5 N - Fixed bridge

3000609

<https://www.phoenixcontact.com/us/products/3000609>



Fixed bridge, number of positions: 20, color: silver

EB 2- 5 - Insertion bridge

1401158

<https://www.phoenixcontact.com/us/products/1401158>



Insertion bridge, pitch: 5 mm, number of positions: 2, color: gray

 Max. current carrying capacity: 22 A

MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



EB 3- 5 - Insertion bridge

1401145

<https://www.phoenixcontact.com/us/products/1401145>

Insertion bridge, pitch: 5 mm, number of positions: 3, color: gray



 Max. current carrying capacity: 22 A

EB 10- 5 - Insertion bridge

1401132

<https://www.phoenixcontact.com/us/products/1401132>

Insertion bridge, pitch: 5.2 mm, number of positions: 10, color: gray



 Max. current carrying capacity: 22 A

MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



D-MBK 2,5/E - End cover

1414035

<https://www.phoenixcontact.com/us/products/1414035>

End cover, width: 1 mm, height: 20.9 mm, color: gray



RPS - Reducing plug

0201647

<https://www.phoenixcontact.com/us/products/0201647>

Reducing plug, number of positions: 1, color: gray



MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



ATP-MBK - Partition plate

1413227

<https://www.phoenixcontact.com/us/products/1413227>



Partition plate, depth: 30.5 mm, width: 2.5 mm, height: 42.5 mm, color: gray

SZS 0,6X3,5 - Screwdriver

1205053

<https://www.phoenixcontact.com/us/products/1205053>



Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



BN-ZB 5,2/WH CUS - Marker pin Zack strip

0824271

<https://www.phoenixcontact.com/us/products/0824271>



Marker pin Zack strip, Strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: plug in, for terminal block width: 5.2 mm, lettering field size: 4 x 4 mm, Number of individual labels: 10

BN-ZB 5,2/WH:UNBEDRUCKT - Marker pin Zack strip

1401815

<https://www.phoenixcontact.com/us/products/1401815>



Marker pin Zack strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: plug in, for terminal block width: 5.2 mm, lettering field size: 4 x 4 mm, Number of individual labels: 10

MBK 2,5/E - Mini feed-through terminal block



1414006

<https://www.phoenixcontact.com/us/products/1414006>

UC-TMN 5,2 - Marker for terminal blocks

0822945

<https://www.phoenixcontact.com/us/products/0822945>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 3.97 x 4.6 mm, Number of individual labels: 96

UC-TMN 5,2 CUS - Marker for terminal blocks

0826857

<https://www.phoenixcontact.com/us/products/0826857>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: plug in, for terminal block width: 5.2 mm, lettering field size: 3.97 x 4.6 mm, Number of individual labels: 96

MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



NS 15 UNPERF 2000MM VPE 10 - DIN rail, unperforated

1401695

<https://www.phoenixcontact.com/us/products/1401695>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 15 PERF 2000MM VPE 10 - DIN rail perforated

1401682

<https://www.phoenixcontact.com/us/products/1401682>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



NS 15 AL PERF 2000MM VPE 10 - DIN rail perforated

1401763

<https://www.phoenixcontact.com/us/products/1401763>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 15 WH PERF 2000MM-VPE 10 - DIN rail perforated

1204096

<https://www.phoenixcontact.com/us/products/1204096>



DIN rail perforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

MBK 2,5/E - Mini feed-through terminal block

1414006


<https://www.phoenixcontact.com/us/products/1414006>



E/MBK - End bracket

1401637

<https://www.phoenixcontact.com/us/products/1401637>



End clamp, width: 6.2 mm, color: gray

E/MK - End bracket

1421633

<https://www.phoenixcontact.com/us/products/1421633>



End clamp, width: 6.2 mm, color: gray

MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>




E/MK 1 - End bracket

1421659

<https://www.phoenixcontact.com/us/products/1421659>

End clamp width: 6 mm, color: gray



PSBJ 3/13/4 - Test plug strip

0201304

<https://www.phoenixcontact.com/us/products/0201304>

Test plug strip, number of positions: 1, color: silver



MBK 2,5/E - Mini feed-through terminal block

1414006

<https://www.phoenixcontact.com/us/products/1414006>



PSB 3/10/4 - Test plug strip

0601292

<https://www.phoenixcontact.com/us/products/0601292>

Test plug strip, number of positions: 1, color: silver



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com