

3046126

https://www.phoenixcontact.com/us/products/3046126

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: G / 5 x 20, nom. voltage: 60 V, nominal current: 6.3 A, connection method: Screw connection, Rated cross section: 4 mm², cross section: 0.14 mm²- 6 mm², mounting type: NS 35/7,5, NS 35/15, color: black

Your advantages

- · An extremely compact design
- · Test pick-off on both sides in the fuse lever
- · Tested for railway applications

Commercial data

Item number	3046126	
Packing unit	50 pc	
Minimum order quantity	50 pc	
Sales key	BE01	
Product key	BE1134	
Catalog page	Page 161 (C-1-2019)	
GTIN	4017918960964	
Weight per piece (including packing)	17 g	
Weight per piece (excluding packing)	17 g	
Customs tariff number	85369095	
Country of origin	DE	



3046126

https://www.phoenixcontact.com/us/products/3046126

Technical data

Notes

General	The current is determined by the fuse used, the voltage by the selected LED. If the fuse is faulty, the downstream circuit will not be disconnected.	
Product properties		
Product type	Fuse terminal block	
Area of application	Railway industry	
	Machine building	
	Plant engineering	
Number of connections	2	
Number of rows	1	
Potentials	1	
Insulation characteristics		
Overvoltage category	III	

Electrical properties

Degree of pollution

Fuse type	Glass / ceramics /		
Rated surge voltage	4 kV		
Maximum power dissipation for nominal condition	1.02 W		
Fuse	G / 5 x 20		
LED voltage range	30 V AC/DC 60 V AC/DC		
LED current range	0.4 mA 0.86 mA		
Maximum power dissipation	max. 1.6 W (with single arrangement of the fuse terminal block in the event of overload)		
	max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)		
	max. 4 W (with single arrangement of the fuse terminal block in the event of a short-circuit)		
	max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)		

3

Input data

LED voltage range	30 V AC/DC 60 V AC/DC
-------------------	-----------------------

Connection data

Number of connections per level	2
Nominal cross section	4 mm²
Screw thread	M3
Tightening torque	0.6 0.8 Nm
Stripping length	9 mm



3046126

https://www.phoenixcontact.com/us/products/3046126

Internal cylindrical gage	A4		
Connection in acc. with standard	IEC 60947-7-3		
Conductor cross section rigid	0.14 mm ² 6 mm ²		
Cross section AWG	26 10 (converted acc. to IEC) 0.14 mm ² 6 mm ²		
Conductor cross section flexible			
Conductor cross section, flexible [AWG]	26 10 (converted acc. to IEC)		
Conductor cross-section flexible (ferrule without plastic sleeve)	0.25 mm ² 4 mm ² 0.14 mm ² 4 mm ²		
Flexible conductor cross section (ferrule with plastic sleeve)			
2 conductors with same cross section, solid	0.14 mm² 1.5 mm²		
2 conductors with same cross section, flexible	0.14 mm ² 1.5 mm ²		
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.14 mm² 1.5 mm²		
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm² 1.5 mm²		
Nominal current	6.3 A		
Maximum load current	6.3 A (the current is determined by the fuse used)		
Nominal voltage	60 V		
Nominal cross section	4 mm ²		

Dimensions

Width	6.2 mm
Height	57.8 mm
Depth on NS 35/7,5	75.6 mm
Depth on NS 35/15	83.1 mm

Material specifications

Color	black	
Flammability rating according to UL 94	V0	
Insulating material group	1	
Insulating material	PA	
Static insulating material application in cold	-60 °C	
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C	
Relative insulation material temperature index (Elec., UL 746 B)	130 °C	
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3 HL 1 - HL 3 HL 1 - HL 3	
Fire protection for rail vehicles (DIN EN 45545-2) R23		
Fire protection for rail vehicles (DIN EN 45545-2) R24		
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3	
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg	
Surface flammability NFPA 130 (ASTM E 162)	passed	
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed	
Smoke gas toxicity NFPA 130 (SMP 800C)	passed	

Mechanical properties

Mechanical data



3046126

https://www.phoenixcontact.com/us/products/3046126

Open side panel	No
Open side parler	NO
nvironmental and real-life conditions	
Ambient conditions	
Ambient temperature (operation)	-60 °C 110 °C (Operating temperature range incl. self-heating;
	for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to
	+70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (operation)	20 % 90 %
Permissible humidity (storage/transport)	30 % 70 %
tandards and regulations	
Connection in acc. with standard	IEC 60947-7-3
ounting	

Mounting type	NS 35/7,5
	NS 35/15




3046126

https://www.phoenixcontact.com/us/products/3046126

Drawings

Circuit diagram






3046126

https://www.phoenixcontact.com/us/products/3046126

Application drawing




Fuse terminal blocks in interconnected arrangement, block consisting of 5 fuse terminal blocks



3046126

https://www.phoenixcontact.com/us/products/3046126

Application drawing



Fuse terminal block in single arrangement,

block consisting of one fuse terminal block and 4 feed-through terminal blocks



3046126

https://www.phoenixcontact.com/us/products/3046126

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/3046126

NV
oproval ID: TAE00001S9

CSA Approval ID: 13631				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Use group B				
	600 V	6.3 A	-	-
Use group C				
	600 V	6.3 A	-	-



EAE

IECEE CB Scheme Approval ID: NL-65056

Approvariab. NE-65056				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	500 V	6.3 A	-	0.14 - 6

EAC Approval ID: RU C-DE.BL08.B.00534

Approval ID: E60425				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Use group B				
	600 V	10 A	26 - 10	-
Multi-conductor connection	600 V	10 A	26 - 14	-
Use group C				
	600 V	10 A	26 - 10	-
Multi-conductor connection	600 V	10 A	26 - 14	-

Keur	KEMA-KEUR Approval ID: 71-11333)			
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
		500 V	6.3 A	-	0.14 - 6



3046126

https://www.phoenixcontact.com/us/products/3046126

Approval ID: LR20037	62TA			
RS Approval ID: 22.44.01.0	0083.250			
CSA Approval ID: 13631				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Use group B				
	60 V	6.3 A	-	-
Use group C				
	60 V	6.3 A	-	-



3046126

https://www.phoenixcontact.com/us/products/3046126

Classifications

ECLASS

ECLASS-11.0	27141116
ECLASS-12.0	27141116
ECLASS-13.0	27250113

ETIM

	ETIM 9.0	EC000899			
UN	UNSPSC				
	UNSPSC 21.0	39121400			



3046126

https://www.phoenixcontact.com/us/products/3046126

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	0e47868d-15c8-4bc0-9186-225dfc2f87e3



3046126

https://www.phoenixcontact.com/us/products/3046126

Accessories

0


Note: Applying some accessories below might limit this product.

FBS 2-6 - Plug-in bridge

3030336 https://www.phoenixcontact.com/us/products/3030336




Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red



FBS 3-6 - Plug-in bridge

3030242 https://www.phoenixcontact.com/us/products/3030242







3046126

https://www.phoenixcontact.com/us/products/3046126

FBS 4-6 - Plug-in bridge

3030255

https://www.phoenixcontact.com/us/products/3030255



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: red

Max. current carrying capacity: 28 A

FBS 5-6 - Plug-in bridge

3030349

https://www.phoenixcontact.com/us/products/3030349



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red



3046126

https://www.phoenixcontact.com/us/products/3046126

FBS 6-6 - Plug-in bridge

1008238

https://www.phoenixcontact.com/us/products/1008238



Plug-in bridge, One side not fully isolated, pitch: 6.2 mm, number of positions: 6, color: red

Max. current carrying capacity: 28 A

FBS 10-6 - Plug-in bridge

3030271 https://www.phoenixcontact.com/us/products/3030271



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red



3046126

https://www.phoenixcontact.com/us/products/3046126

FBS 20-6 - Plug-in bridge

3030365

https://www.phoenixcontact.com/us/products/3030365



Plug-in bridge, pitch: 6.2 mm, number of positions: 20, color: red

1 Max. current carrying capacity: 28 A

FBS 50-6 - Plug-in bridge

3032224

https://www.phoenixcontact.com/us/products/3032224



Plug-in bridge, pitch: 6.2 mm, number of positions: 50, color: red



3046126

https://www.phoenixcontact.com/us/products/3046126

FBSR 2-6 - Plug-in bridge

3033715

https://www.phoenixcontact.com/us/products/3033715



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: red

1 Max. current carrying capacity: 24 A

FBSR 3-6 - Plug-in bridge

3001594 https://www.phoenixcontact.com/us/products/3001594



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: red



3046126

https://www.phoenixcontact.com/us/products/3046126

FBSR 4-6 - Plug-in bridge

3001595

https://www.phoenixcontact.com/us/products/3001595



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: red

1 Max. current carrying capacity: 24 A

FBSR 5-6 - Plug-in bridge

3001596 https://www.phoenixcontact.com/us/products/3001596



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: red



3046126

https://www.phoenixcontact.com/us/products/3046126

FBSR 10-6 - Plug-in bridge

3033716

https://www.phoenixcontact.com/us/products/3033716



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: red

1 Max. current carrying capacity: 24 A

FBSRH 2-6 - Short-circuit connector

3033812

https://www.phoenixcontact.com/us/products/3033812



Short-circuit connector, pitch: 6.2 mm, number of positions: 2, color: red



3046126

https://www.phoenixcontact.com/us/products/3046126

FBS 2-6 BU - Plug-in bridge

3036932

https://www.phoenixcontact.com/us/products/3036932



Plug-in bridge, pitch: 6.2 mm, number of positions: 2, color: blue

Max. current carrying capacity: 28 A

FBS 3-6 BU - Plug-in bridge

3036945

https://www.phoenixcontact.com/us/products/3036945



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: blue



3046126

https://www.phoenixcontact.com/us/products/3046126

FBS 4-6 BU - Plug-in bridge

3036958

https://www.phoenixcontact.com/us/products/3036958



Plug-in bridge, pitch: 6.2 mm, number of positions: 4, color: blue

Max. current carrying capacity: 28 A

FBS 5-6 BU - Plug-in bridge

3036961

https://www.phoenixcontact.com/us/products/3036961



Plug-in bridge, pitch: 6.2 mm, number of positions: 5, color: blue



3046126

https://www.phoenixcontact.com/us/products/3046126

FBS 10-6 BU - Plug-in bridge

3032198

https://www.phoenixcontact.com/us/products/3032198



Plug-in bridge, pitch: 6.2 mm, number of positions: 10, color: blue

Max. current carrying capacity: 28 A

FBS 20-6 BU - Plug-in bridge

3032208

https://www.phoenixcontact.com/us/products/3032208



Plug-in bridge, pitch: 6.2 mm, number of positions: 20, color: blue



3046126

https://www.phoenixcontact.com/us/products/3046126

FBS 50-6 BU - Plug-in bridge

3032211

https://www.phoenixcontact.com/us/products/3032211



Plug-in bridge, pitch: 6.2 mm, number of positions: 50, color: blue

1 Max. current carrying capacity: 28 A

DMET 5X20 - Feed-through connector

3032075

https://www.phoenixcontact.com/us/products/3032075



Feed-through metal in the shape of a 5 x 20 mm glass tube fuse insert for use in fuse terminal blocks.



3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/7,5 PERF 2000MM - DIN rail perforated

0801733

https://www.phoenixcontact.com/us/products/0801733



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

https://www.phoenixcontact.com/us/products/0801681



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver



3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/7,5 WH PERF 2000MM - DIN rail perforated

1204119

https://www.phoenixcontact.com/us/products/1204119



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

https://www.phoenixcontact.com/us/products/1204122



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver



3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

https://www.phoenixcontact.com/us/products/0801704



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

NS 35/7,5 ZN PERF 2000MM - DIN rail perforated

1206421 https://www.phoenixcontact.com/us/products/1206421



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver



3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

https://www.phoenixcontact.com/us/products/1206434



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

https://www.phoenixcontact.com/us/products/0801762



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored



3046126 https://www.phoenixcontact.com/us/products/3046126

NS 35/ 7,5 CAP - End cap

1206560 https://www.phoenixcontact.com/us/products/1206560

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 PERF 2000MM - DIN rail perforated

1201730 https://www.phoenixcontact.com/us/products/1201730



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver



3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

https://www.phoenixcontact.com/us/products/1201714



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

https://www.phoenixcontact.com/us/products/0806602



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white



3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

https://www.phoenixcontact.com/us/products/1204135



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

https://www.phoenixcontact.com/us/products/1201756



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver



3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

https://www.phoenixcontact.com/us/products/1206599



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

https://www.phoenixcontact.com/us/products/1206586



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver



3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

https://www.phoenixcontact.com/us/products/1201895



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

NS 35/15 CAP - End cap

1206573 https://www.phoenixcontact.com/us/products/1206573

DIN rail end piece, for DIN rail NS 35/15





3046126

https://www.phoenixcontact.com/us/products/3046126

NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

https://www.phoenixcontact.com/us/products/1201798



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

ZB 5 : UNBEDRUCKT - Zack marker strip

1050004

https://www.phoenixcontact.com/us/products/1050004



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.1 x 10.5 mm, Number of individual labels: 10



3046126

https://www.phoenixcontact.com/us/products/3046126

ZB 5 CUS - Zack marker strip

0824962

https://www.phoenixcontact.com/us/products/0824962



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: $5.15 \times 10.5 \text{ mm}$, Number of individual labels: 10

ZB 5,LGS:FORTL.ZAHLEN - Zack marker strip

1050017 https://www.phoenixcontact.com/us/products/1050017



Zack marker strip, Strip, white, labeled, printed horizontally: consecutive numbers 1 \dots 10, 11 \dots 20, etc. up to 491 \dots 500, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10



3046126

https://www.phoenixcontact.com/us/products/3046126

ZB 5,QR:FORTL.ZAHLEN - Zack marker strip

1050020

https://www.phoenixcontact.com/us/products/1050020



Zack marker strip, white, Printed vertically: consecutive numbers 1 \dots 10, 11 \dots 20, etc. up to 491 \dots 500, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm

ZB 5,LGS:GLEICHE ZAHLEN - Zack marker strip

1050033 https://www.phoenixcontact.com/us/products/1050033



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10



3046126

https://www.phoenixcontact.com/us/products/3046126

ZB 5,LGS:L1-N,PE - Zack marker strip

1050415

https://www.phoenixcontact.com/us/products/1050415



Zack marker strip, Strip, white, labeled, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 5.15 x 10.5 mm, Number of individual labels: 10

UC-TM 5 - Marker for terminal blocks

0818108 https://www.phoenixcontact.com/us/products/0818108



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 96



3046126

https://www.phoenixcontact.com/us/products/3046126

UC-TM 5 CUS - Marker for terminal blocks

0824581

https://www.phoenixcontact.com/us/products/0824581



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: 10.5 x 4.6 mm, Number of individual labels: 96

UCT-TM 5 - Marker for terminal blocks

0828734 https://www.phoenixcontact.com/us/products/0828734



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 72



3046126

https://www.phoenixcontact.com/us/products/3046126

UCT-TM 5 CUS - Marker for terminal blocks

0829595

https://www.phoenixcontact.com/us/products/0829595

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 5.2 mm, lettering field size: 4.6 x 10.5 mm, Number of individual labels: 72

GBS 5-25X12 - Group marker label for terminal marking

0810588

https://www.phoenixcontact.com/us/products/0810588



Group marker label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with a 25 x 12 mm label or manually with the B-STIFT, in the foot part with ZB 5



3046126

https://www.phoenixcontact.com/us/products/3046126

GBS 5-25X5 - Group marker label for terminal marking

0829126

https://www.phoenixcontact.com/us/products/0829126



Group marking label, can be snapped into terminal center for screw, spring-cage, push-in, and fast connection terminal blocks, can be labeled with a 24 x 4 mm label or manually using B-STIFT, in the foot part with ZB 5

STP 5-2-ZB - Marker carriers

3037643 https://www.phoenixcontact.com/us/products/3037643



Marker carriers, snaps into ST 2,5 spring-cage terminal blocks, can be marked with UC-TM 5, UC-TMF 5, UCT-TM 5, UCT-TMF 5, ZB 5, or ZBF 5, gray, unlabeled, mounting type: snapped



3046126

https://www.phoenixcontact.com/us/products/3046126

ZB 6:UNBEDRUCKT - Zack marker strip

1051003

https://www.phoenixcontact.com/us/products/1051003



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: $6.15 \times 10.5 \text{ mm}$, Number of individual labels: 10 mm

ZB 6 CUS - Zack marker strip

0824992 https://www.phoenixcontact.com/us/products/0824992



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: $6.15 \times 10.5 \text{ mm}$, Number of individual labels: 10



3046126

https://www.phoenixcontact.com/us/products/3046126

ZB 6,LGS:FORTL.ZAHLEN - Zack marker strip

1051016

https://www.phoenixcontact.com/us/products/1051016



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers $1 \dots 10$, $11 \dots 20$, etc. up to $491 \dots 500$, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6. 15×10.5 mm, Number of individual labels: 10

ZB 6, QR: FORTL. ZAHLEN - Zack marker strip

1051029 https://www.phoenixcontact.com/us/products/1051029



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 491 ... 500, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6. 15 x 10.5 mm, Number of individual labels: 10



3046126

https://www.phoenixcontact.com/us/products/3046126

ZB 6,LGS:GLEICHE ZAHLEN - Zack marker strip

1051032

https://www.phoenixcontact.com/us/products/1051032



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: Identical numbers 1 or 2, etc. up to 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10

ZB 6,LGS:L1-N,PE - Marker for terminal blocks

1051414 https://www.phoenixcontact.com/us/products/1051414



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm, Number of individual labels: 10



3046126

https://www.phoenixcontact.com/us/products/3046126

ZB 6,LGS:U-N - Marker for terminal blocks

1051430

https://www.phoenixcontact.com/us/products/1051430



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: U, V, W, N, GND, U, V, W, N, GND, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10. 5 mm, Number of individual labels: 10

UC-TM 6 - Marker for terminal blocks

0818085

https://www.phoenixcontact.com/us/products/0818085



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80



3046126

https://www.phoenixcontact.com/us/products/3046126

UC-TM 6 CUS - Marker for terminal blocks

0824589

https://www.phoenixcontact.com/us/products/0824589



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 80

UCT-TM 6 - Marker for terminal blocks

0828736

https://www.phoenixcontact.com/us/products/0828736



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual labels: 60

labels: 60



3046126

https://www.phoenixcontact.com/us/products/3046126

UCT-TM 6 CUS - Marker for terminal blocks

0829602

https://www.phoenixcontact.com/us/products/0829602

CLIPFIX 35 - End bracket

3022218 https://www.phoenixcontact.com/us/products/3022218



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 6.2 mm, lettering field size: 5.6 x 10.5 mm, Number of individual



3046126

https://www.phoenixcontact.com/us/products/3046126

CLIPFIX 35-5 - End bracket

3022276

https://www.phoenixcontact.com/us/products/3022276



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5. 15 mm, color: gray

E/NS 35 N - End bracket

0800886 https://www.phoenixcontact.com/us/products/0800886



End clamp, width: 9.5 mm, color: gray



3046126

https://www.phoenixcontact.com/us/products/3046126

SZS 0,6X3,5 - Screwdriver

1205053

https://www.phoenixcontact.com/us/products/1205053



Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: $0.6 \times 3.5 \times 100$ mm, 2-component grip, with non-slip grip

X-PEN 0,35 - Marker pen

0811228 https://www.phoenixcontact.com/us/products/0811228



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm



3046126

https://www.phoenixcontact.com/us/products/3046126

SF-SL 0,6X3,5-100 S-VDE - Screwdriver

1212587

https://www.phoenixcontact.com/us/products/1212587



Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: $0.6 \times 3.5 \times 100 \text{ mm}$, 2-component grip, with non-slip grip

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com