



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Ground**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Primary Product Color: **Green & Yellow**

Product Spacing: **6 mm [ .236 in ]**

Number of Positions: **2**

Features

Product Type Features

|                                     |                            |
|-------------------------------------|----------------------------|
| Modular Terminal Block Product Type | Screw Clamp Terminal Block |
|-------------------------------------|----------------------------|

Configuration Features

|                     |        |
|---------------------|--------|
| Gauge Type          | A4-B3  |
| Number of Levels    | 1      |
| Number of Circuits  | 1      |
| Block Function      | Ground |
| Number of Positions | 2      |

Electrical Characteristics

|                                             |        |
|---------------------------------------------|--------|
| Impulse Withstanding Voltage Rating (IEC)   | 8000 V |
| Dielectric Withstanding Voltage (Max)       | 2200 V |
| Short-Time Withstanding Current Rating @ 1s | 720 A  |

Body Features

|                       |                 |
|-----------------------|-----------------|
| Product Weight        | 13.7 g[.539 oz] |
| Primary Product Color | Green & Yellow  |

Mechanical Attachment

|                         |                   |
|-------------------------|-------------------|
| DIN Rail Mounting Type  | TH35-15, TH35-7.5 |
| Connector Mounting Type | DIN Rail          |



Housing Features

|                  |           |
|------------------|-----------|
| Housing Material | Polyamide |
|------------------|-----------|

Dimensions

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp | 24 - 10 AWG             |
| Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp       | 24 - 10 AWG             |
| Wire Stripping Length                                              | 10.5 mm[.413 in]        |
| Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp        | 24 - 12 AWG             |
| Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp    | .22 - 4 mm <sup>2</sup> |
| Tool Size                                                          | 4 mm[.157 in]           |
| Product Depth                                                      | 47.4 mm                 |
| Product Length                                                     | 47.4 mm[1.87 in]        |
| Product Height                                                     | 59.5 mm                 |
| Product Spacing                                                    | 6 mm[.236 in]           |

Usage Conditions

|                                |                            |
|--------------------------------|----------------------------|
| Installation Temperature Range | -5 - 40 °C[23 - 104 °F]    |
| Operating Temperature Range    | -55 - 110 °C[-67 - 230 °F] |

Industry Standards

|                        |          |
|------------------------|----------|
| IP Rating              | IP20     |
| UL Flammability Rating | UL 94V-0 |

Product Compliance

For compliance documentation, visit the product page on TE.com>



|                                               |                                                                                                                               |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                     |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                     |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                       |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240)<br>Candidate List Declared Against: JAN 2024 (240)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                           |
| Solder Process Capability                     | Not reviewed for solder process capability                                                                                    |



Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

|                                                                                                                           |                                                                                                                            |                                                                                                                                   |                                                                                                                                   |
|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <br>TE Part # 1SNK150000R0000<br>MC612 | <br>TE Part # 1SNK505910R0000<br>ES4    | <br>TE Part # 1SNK900001R0000<br>BAM4        | <br>TE Part # 1SNK900002R0000<br>BAZ1        |
| <br>TE Part # 1SNK900103R0000<br>CS-R1 | <br>TE Part # 1SNK900105R0000<br>ES-TC6 | <br>TE Part # 1SNK900200R0000<br>TC5         | <br>TE Part # 1SNK900203R0000<br>TP2         |
| <br>TE Part # 1SNK900205R0000<br>TP4   | <br>TE Part # 1SNK900624R0000<br>KCO    | <br>TE Part # 1SET111013R0000<br>WF040-10-OR | <br>TE Part # 1SET111032R0000<br>WF040-10-GR |



Also in the Series | ENTRELEC SNK



Customers Also Bought





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1SNK506150R0000\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1SNK506150R0000\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1SNK506150R0000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

ZS6-PE

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

English

Essential Entrelec Terminal Blocks

Japanese

Agency Approvals

ZK-ZS\_ATEX\_1SND225112U1006-C-TE

English

1SNK506150R0000

Modular Terminal Blocks, Ground, Screw Clamp Terminal Block, Green & Yellow,  
Product Spacing .236 in [6 mm], 2 Position, DIN Rail, ENTRELEC SNK

