9999TC20

Disconnect mechanism, flange mounted, disconnect switch auxiliary contact kit, 10A, 2 pole, DPDT



Main

| Wilding | •• | |
|------------------------------|-----------|--|
| Range | Square D | |
| Product or Component Type | Interlock | |
| Device Application | Control | |

Complementary

| Range compatibility | Square D Disconnect Switch | |
|--------------------------------|----------------------------|--|
| [le] rated operational current | 10 A120 V AC 50/60 Hz | |
| | 10 A240 V AC 50/60 Hz | |
| | 10 A480 V AC 50/60 Hz | |
| | 10 A600 V AC 50/60 Hz | |

Ordering and shipping details

| Category | US10CP121761 |
|-------------------|--------------|
| Discount Schedule | 0CP1 |
| GTIN | 785901858485 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| PCE | |
|---------------------|---|
| 1 | |
| 3.10 in (7.874 cm) | |
| 4.20 in (10.668 cm) | |
| 6.70 in (17.018 cm) | |
| 8.80 oz (249.476 g) | |
| | 1 3.10 in (7.874 cm) 4.20 in (10.668 cm) 6.70 in (17.018 cm) |

Offer Sustainability

| EU RoHS Directive | Under investigation |
|-----------------------|------------------------|
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| Sonita Gladi Warranty | | |
|-----------------------|-----------|--|
| Warranty | 18 months | |