GS2AH140

External rotary handle, TeSys GS, red handle, front mounting, 2 positions I-O, NEMA 3R, for GS 30 to 400A UL





Main

Range of Product	TeSys
Range	TeSys
Device short name	GS2AH
Product or Component Type	Rotary handle
Range compatibility	TeSys TeSys GS GS2EU TeSys TeSys GS GS2GU TeSys TeSys GS GS2JU TeSys TeSys GS GS2MU TeSys TeSys GS GS2QU
Type of operating handle	External frontal
Handle colour	Red
Handle front plate colour	Yellow

Complementary

Handle positions	O-I	
Rotary handle padlocking	With	
Switch rated current	30 A	
	60 A	
	100 A	
	200 A	
	400 A	
Standards	CSA	
	UL	
Net Weight	0.53 lb(US) (0.24 kg)	

Environment

NEMA Degree of Protection	NEMA 3R/12
NEWA Degree of Frotection	INCIVIA SIVIZ

Ordering and shipping details

Category	US10I1122640
Discount Schedule	0111
GTIN	3389119411844
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.97 in (5.000 cm)	
Package 1 Width	4.72 in (12.000 cm)	
Package 1 Length	6.30 in (16.000 cm)	
Package 1 Weight	8.71 oz (247.000 g)	
Unit Type of Package 2	S03	
Number of Units in Package 2	15	

Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	9.15 lb(US) (4.150 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information

Contractual warranty

Warranty	18 months