

LK4QU3N

Disconnect Switch, TeSys LK, nonfusible, 400A, 600 V, HP rated, 3 pole, rotary handle, up to 200kA SCCR



Main

Range	TeSys
Product name	TeSys LK
Product or Component Type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

Complementary

Poles description	3P
Network type	AC DC
Network Frequency	50/60 Hz
[Ie] rated operational current	200 A690 V AC AC-23A IEC 400 A400 V AC AC-22A IEC 400 A400 V AC AC-23A IEC 400 A690 V AC AC-22A IEC 400 A CSA 400 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	1000 V
Control Type	Rotary handle
Type of operating handle	External frontal External right side
Mounting Support	Plate
[Uimp] rated impulse withstand voltage	12 kV IEC
Rated power in W	185 KW 690 V 220 KW 400 V 280 kW 500 V
Rated power in hp	125 Hp 240 V 312 A AC 250 Hp 480 V 302 A AC 350 Hp 600 V 336 A AC 20 Hp 125 V 148 A DC 50 hp 250 V 173 A DC
[Icw] rated short-time withstand current	48 kA
Mechanical durability	6000 cycles
Electrical durability	1000 cycles
Connections - terminals	Lugs-ring terminals 1 0.02 in ² (16 mm ²)
Height	10.24 in (260 mm)
Width	9.06 in (230 mm)
Depth	5.04 in (128 mm)

Environment

Standards	UL98 IEC 60947-3 CSA C22.2 No 4
Product Certifications	CE[RETURN]UL[RETURN]CSA

Ordering and shipping details

Category	US10I1122640
Discount Schedule	0I11
GTIN	3606480510465
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.10 in (28.200 cm)
Package 1 Width	21.30 in (54.100 cm)
Package 1 Length	16.54 in (42.000 cm)
Package 1 Weight	14.11 lb(US) (6.402 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	4
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	31.50 in (80.000 cm)
Package 2 Length	47.24 in (120.000 cm)
Package 2 Weight	82.91 lb(US) (37.608 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------