



Main

| | |
|-------------------|------------------------------------|
| Range | TeSys |
| Product Name | TeSys VARIO |
| Device Short Name | VCF |
| Product Type | Emergency stop switch disconnecter |

Complementary

| | |
|--|--|
| Device Composition | Switch Handle |
| Mounting Support | Handle door Switch door |
| Mounting Method | By 4 screws handle |
| Performance Level | High performance |
| Number of Poles | 3P |
| Contact Type and Composition | 3 NO |
| [Ue] IEC Rated Operational Voltage | 690 V AC 50/60 Hz |
| IEC Rated Operational Power in W | 3 KW 400...415 V AC-3) 4 KW 500 V AC-3) 1.5 KW 230...240 V AC-3) 5.5 KW 500 V AC-23A) 5.5 KW 690 V AC-3) 7.5 KW 690 V AC-23A) 3 KW 230...240 V AC-23A) 4 kW 400...415 V AC-23A) |
| [Ie] Rated Operational Current | 8.1 A AC-23 Ue: 400 V |
| [Ith] Conventional Free Air Thermal Current | 12 A |
| [Ithe] Conventional Enclosed Thermal Current | 10 A |
| Making Capacity (I Rms) | 120 A 400 V AC-21A 120 A 400 V AC-22A 120 A 400 V AC-23A |
| Breaking Capacity | 120 A 400 V AC-21A) 120 A 400 V AC-22A) 120 A 400 V AC-23A) |
| Rated Conditional Short Circuit Current | 10 KA 400 V 12 A aM 10 kA 400 V 12 A gG |
| [Icm] Rated Short Circuit Making Capacity | 1 kA 400 V at Ipeak |
| [Icw] Rated Short Time Withstand Current | 300 A 400 V 1 s |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV |
| Suitability for Isolation | Yes |
| Network Type | DC AC |
| Intermittent Duty Class | 30 |
| Control Type | Rotary handle |

| | |
|------------------------------|---|
| Rotary Handle Mounting Style | Direct |
| Handle Color | Red |
| Handle Front Plate Color | Yellow |
| Rotary Handle Padlocking | 1 to 3 padlocks 0.16...0.31 in (4...8 mm) |
| Marking | 0 - 1 |
| Mechanical Durability | 100000 cycles |
| Electrical Durability | 100000 Cycles AC-21 30000 Cycles DC-1 30000 Cycles DC-2 30000 Cycles DC-3 30000 Cycles DC-4 30000 cycles DC-5 |
| IEC Terminal Connection | Power circuit screw clamp terminals 0.02 in ² (10 mm ²) solid Power circuit screw clamp terminals 0.01 in ² (6 mm ²) flexible - with cable end |
| Tightening Torque | Power circuit 18.59 lbf.in (2.1 N.m) screw clamp terminals |
| Base Dimension | 60 x 60 mm |
| Height | 2.91 in (74 mm) |
| Width | 2.36 in (60 mm) |
| Product Weight | 0.55 lb(US) (0.25 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-3 |
| Product Certifications | UL[RETURN]CCC[RETURN]GL[RETURN]CSA[RETURN]UKCA |
| Degree of Protection | IP20 conforming to IEC 60529 IP65 |
| Protective Treatment | TC |
| Mechanical Robustness | Vibrations 10...150 Hz 1 gn) IEC 60068-2-6 Shocks 11 ms 30 Gn) IEC 60068-2-27 |
| Ambient Air Temperature for Operation | -4...122 °F (-20...50 °C) |
| Fire Resistance | 1760 °F (960 °C) IEC 60695-2-1 |
| Compatibility Code | Main switch disconnecter |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10CP121730 |
| Discount Schedule | 0CP1 |
| GTIN | 3389110448870 |
| Returnability | Yes |
| Country of origin | CZ |

Packing Units

| | |
|------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.35 in (8.500 cm) |
| Package 1 Width | 3.54 in (9.000 cm) |
| Package 1 Length | 4.92 in (12.500 cm) |
| Package 1 Weight | 7.72 oz (219.000 g) |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 24 |
| Package 2 Height | 11.81 in (30.000 cm) |
| Package 2 Width | 11.81 in (30.000 cm) |
| Package 2 Length | 15.75 in (40.000 cm) |
| Package 2 Weight | 12.64 lb(US) (5.732 kg) |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 192 |
| Package 3 Height | 29.53 in (75.000 cm) |
| Package 3 Width | 23.62 in (60.000 cm) |
| Package 3 Length | 31.50 in (80.000 cm) |
| Package 3 Weight | 121.47 lb(US) (55.100 kg) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| PVC free | Yes |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|