

Product data sheet

Specifications



Disconnect switch, TeSys VLS,
additional earthing ground terminal,
for 30A to 125A, size 2 (70mm),
door mount

VLS1GD2

! Discontinued

! Discontinued on: Dec 18, 2023

Main

Range	TeSys
Device Short Name	VLS1G
Product Or Component Type	Additional earthing block
Performance Level	High performance
Contacts Type And Composition	Without
Range Compatibility	TeSys TeSys VARIO LS VLS3P TeSys TeSys VARIO LS VLS1P TeSys TeSys VARIO LS VLSA
Network Type	AC
Network Frequency	50/60 Hz

Complementary

Mounting Location	Left Right
Main Device Mounting Mode	Door
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	125 A (at 131 °F (55 °C))
[Ithe] Conventional Enclosed Thermal Current	125 A
Connections - Terminals	screw clamp terminals 0.08 in² (50 mm²) solid screw clamp terminals 0.11 in² (70 mm²) flexible - without cable end
Tightening Torque	44.25...53.10 lbf.in (5...6 N.m) screw clamp terminals
Height	3.94 in (100 mm)
Width	0.91 in (23 mm)
Depth	1.91 in (48.6 mm)
Net Weight	0.24 lb(US) (0.11 kg)
Colour	Grey

Environment

Standards	UL98 CSA C22.2 No 4 IEC 60947-3
-----------	---------------------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	cULus GL
Ip Degree Of Protection	IP20 conforming to IEC 60529
Mechanical Robustness	Vibrations 2...100 Hz Fc 0.7 g) IEC 60068-2-6 Shocks 11 ms Ea 15 gn) IEC 60068-2-27
Ambient Air Temperature For Operation	-13...131 °F (-25...55 °C)
Fire Resistance	1760 °F (960 °C) IEC 60695-2-11

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.94 in (10.0 cm)
Package 1 Width	0.91 in (2.3 cm)
Package 1 Length	1.91 in (4.86 cm)
Package 1 Weight	4.09 oz (116.0 g)
Unit Type Of Package 2	S03
Number Of Units In Package 2	36
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	10.78 lb(US) (4.889 kg)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
Reach Regulation		REACH Declaration
Eu Rohs Directive		Compliant EU RoHS Declaration
China Rohs Regulation		China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)