

Disconnect switch, TeSys VLS, protruding rotary handle, screw mounting, 48x48 mm, black handle, 5 mm shaft

VLSH4S5B

Main

Range	TeSys
Device Short Name	VLSH
Product Or Component Type	Rotary handle
Range Compatibility	TeSys TeSys VARIO LS VLS3P
Handle Colour	Black
Handle Front Plate Colour	Grey
Rotary Handle Padlocking	1 padlock 0.160.31 in (48 mm)
Marking	0 - 1

Complementary

Fixing Mode	By 4 screws
Tightening Torque	20.36 lbf.in (2.3 N.m)
Base Dimension	48 x 48 mm
Height	1.9 in (48 mm)
Width	1.9 in (48 mm)
Depth	1.5 in (39 mm)
Net Weight	0.13 lb(US) (0.06 kg)

Environment

Ip Degree Of Protection	IP65
Nema Degree Of Protection	NEMA 1
	NEMA 2 UL 508
	NEMA 3R UL 508
	NEMA 4 UL 508
	NEMA 4X UL 508
	NEMA 12 UL 508
	NEMA 12K UL 508

Packing Units

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.181 in (3.000 cm)
Package 1 Width	3.740 in (9.500 cm)
Package 1 Length	1.969 in (5.000 cm)
Package 1 Weight	1.340 oz (38.000 g)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)