
TOLEF UNLESS O' SPEC	
0-10	±0.20
10-30	+0.30


30-100 ±0.40


THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER
ORIGINAL ①











SPECIFICATIONS:

MATERIAL:

HOUSING: GLASS REINFORCED THERMOPLASTIC, PA66

CONTACT: COPPER ALLOY

PLATING: 30µ" GOLD PLATING ON CONTACT AREA,

TIN PLATING ON SOLDERING AREA

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

DIELECTRIC

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

MECHANICAL

RETENTION FORCE: 460g MIN PER CONTACT INSERTION FORCE: 230g MAX PER CONTACT PAIR WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C

NOTE:

4 TO 124 POSITIONS ARE AVAILABLE EXCEPT 18, 28, 34, 38, 42 TO 46, 54 TO 58 POSITIONS

	ACAD REFERENCE NO.: 302 Assembly			UNIT: MM		
302 SERIES CARD EDG	DRAWN: J.L.	DATE: June 6, 202)23		
	CHECKED:		DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: 1:1		SHEET	1 OF	1
TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 3	302-008-6	556-201		ISSUE
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER:	302-008-6	56-201		1