


THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.





ISSUE NUMBER

(1)

ORIGINAL








SECTION A-A SCALE 1 : 1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



SPECIFICATIONS: MATERIAL: HOUSING: CONTACT: PLATING:

ELECTRICAL

VOLTAGE RATING: CURRENT RATING: DIELECTRIC WITHSTANDING VOLTAGE: **INSULATION RESISTANCE:** CONTACT RESISTANCE:

MECHANICAL

RETENTION FORCE: INSERTION FORCE: WITHDRAWAL FORCE:

ENVIRONMENTAL TEMPERATURE RANGE:

-55°C TO +85°C

NOTE:

4 TO 124 POSITIONS ARE AVAILABLE EXCEPT 18, 28, 34, 38, 42 TO 46, 54 TO **58 POSITIONS**

		ACAD REFERENCE NO.: 302 Assembly		UNIT: MM
302 SERIES CARD EDG	DRAWN: J.L.	DATE: June 6, 2	023	
		CHECKED:	DATE:	
EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1	SHEET 1 OF	= 1
		DRAWING NUMBER: 302-068-	256-201	ISSUE
		PART NUMBER: 302-068-	256-201	1

GLASS REINFORCED THERMOPLASTIC, PA66 COPPER ALLOY

GOLD FLASH PLATING ON CONTACT AREA, TIN PLATING ON SOLDERING AREA

250 VAC RMS 1A

500VAC RMS 60Hz FOR 60s 1000 MEGA OHMS MIN AT 500VDC 30 mohms max

460g MIN PER CONTACT 230g MAX PER CONTACT PAIR 15g MIN PER CONTACT PAIR