

15.50

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

1

ORIGINAL

44.20 ±0.20 39.37 ±0.15	c	SPECIFICATIONS:			
A		SPECIFICATIONS: MATERIAL: HOUSING:	HI-TEMP THERMOPL	ASTIC, PPS	
	CONTACT: PLATING: CONTACT: COPPER ALLOY 30µ" GOLD PLATING ON CONTA TIN PLATING ON SOLDERING AR				
15.50	<u>+</u>	ELECTRICAL	TIN PLATING ON SOLDERING AREA		
	VOLTAGE RATING: 250 VAC RMS				
1.70 A	30	CURRENT RATING: DIELECTRIC	1A		
			TAGE: 500VAC RMS 60Hz FOR 60s CE: 1000 MEGA OHMS MIN AT 500VDC		
	6.20	- CONTACT RESISTANCE	E: 30 mOHMS MAX		
7.62 CARD SLOT 0.60 POINT OF	MECHANICAL RETENTION FORCE: INSERTION FORCE: WITHDRAWAL FORCE:		460g MIN PER CONTACT 230g MAX PER CONTACT PAIR 15g MIN PER CONTACT PAIR		
		ENVIRONMENTAL TEMPERATURE RANGE:	-55°C TO +105°C		
	NOTE: 4 TO 124 POSITIONS ARE AVAILABLE EXCEPT 18, 28, 34, 38, 42 TO 46,				
SECTION A-A		54 TO 58 POSITIONS		20, 04, 00, 42 10 40,	
SCALE 1 : 1			ACAD REFERENCE NO.: 802 A	Assembly UNIT: MM	
	802 SERIES CARD EDGE CONNECTOR		DRAWN: J.L.	DATE: June 6, 2023	
THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.	1		CHECKED:	DATE:	
		THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED	SCALE: 1:1	SHEET 1 OF 1	
	YOUR CONNECTION TO QUALITY & SERVICE	OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 802-060- PART NUMBER: 802-060-	1	