


TOLERANCE UNLESS OTHERWISE SPECIFIED

0-10 ±0.20 10-30 ±0.30 30-100 ±0.40 THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ORIGINAL (1)



SPECIFICATIONS:

MATERIAL:

HOUSING: HI-TEMP THERMOPLASTIC, PPS

CONTACT: COPPER ALLOY

PLATING: 30µ" GOLD PLATING ON CONTACT AREA,

TIN PLATING ON SOLDERING AREA

**ELECTRICAL** 

VOLTAGE RATING: 250 VAC RMS

CURRENT RATING: 1A

**DIELECTRIC** 

WITHSTANDING VOLTAGE: 500VAC RMS 60Hz FOR 60s

INSULATION RESISTANCE: 1000 MEGA OHMS MIN AT 500VDC

CONTACT RESISTANCE: 30 mOHMS MAX

**MECHANICAL** 

RETENTION FORCE: 460g MIN PER CONTACT
INSERTION FORCE: 230g MAX PER CONTACT PAIR
WITHDRAWAL FORCE: 15g MIN PER CONTACT PAIR

**ENVIRONMENTAL** 

TEMPERATURE RANGE: -55°C TO +105°C

NOTE:

4 TO 124 POSITIONS ARE AVAILABLE EXCEPT 18, 28, 34, 38, 42 TO 46,

54 TO 58 POSITIONS

802 SERIES CARD EDGE CONNECTOR		ACAD REFERENCE NO.: 802	Assembly	UNIT: MM
		DRAWN: J.L.	DATE: June 6, 2023	
		CHECKED:	DATE:	
EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1	SHEET 1 OF	1
		DRAWING NUMBER: 802-068	-656-201	ISSUE
		PART NUMBER: 802-068	-656-201	1