

Type ANF

Automotive / Marine Limiter

Fast Acting



www.optifuse.com

(619) 593-5050

Specifications:

- **Voltage Rating:** 32 VDC
- **Amperage Rating:** 40A, 50A, 60A, 80A, 100A, 125A, 130A, 150A, 175A, 180A, 200A, 225A, 250A, 275A, 300A, 400A, 425A, 500A, 600A, 700A, 800A.
- **Interrupting Capacity:** 2000A @ 32VDC (40A-400A)
1500A @ 32VDC (500A-600A)
2500A @ 32VDC (700A-800A)

• Construction:

Body Material: Bakelite

Terminals: Gold-plated

40A ~ 80A – Brass

100A ~ 800A – Copper Alloy

Time Characteristics	
% of Rated Current	Clearing Time
100%	Min 4h
250%	Max 300s



Ignition Protected

Recommended Mounting:

Optifuse Fuse Block BLC-09 to 200A

Optifuse Fuse Block BLC-209 to 800A

Mechanical Dimensions: Inches [mm]



* Dim F: 35-500A 8.8 ±0.2 ; 600A-800A 11.11 ±0.3

Warning:



-Operation beyond the specified maximum ratings or improper use may result in damage and possible electrical arcing and/or flame.

-Avoid contact of device with chemical solvent. Prolonged contact may damage the device performance.