




742 700 33
 Ø Cable: 4.4 mm Material: 3 W 800




742 700 31
 Ø Cable: 4.6 mm Material: 4 W 1500




742 700 5
 Ø Cable: 8.6 mm Material: 4 W 620




742 700 53
 Ø Cable: 7.6 mm Material: 3 W 800




742 700 62
 Ø Cable: 5.7 mm Material: 4 W 1500




742 700 30
 Ø Cable: 4.6 mm Material: 3 W 800




742 700 32
 Ø Cable: 4.6 mm Material: 4 W 620




742 700 45
 Ø Cable: 7.0 mm Material: 4 W 620




742 700 781
 Ø Cable: 8.0 mm Material: 7 W 700




742 700 44
 Ø Cable: 7.5 mm Material: 4 W 620




742 700 34
 Ø Cable: 6.9 mm Material: 3 W 800




742 700 4
 Ø Cable: 5.9 mm Material: 4 W 620




742 700 51
 Ø Cable: 10.0 mm Material: 3 W 800




742 700 9
 Ø Cable: 9.1 mm Material: 3 W 800




742 700 57
 Ø Cable: 11.0 mm Material: 4 W 620



742 700 381
 Ø Cable: 3.3 mm Material: 4 W 1500



742 700 77
 Ø Cable: 6.0 mm Material: 7 W 380



742 700 43
 Ø Cable: 6.9 mm Material: 3 W 800

EMC COMPONENTS | INDUCTORS | TRANSFORMERS | RF COMPONENTS | CIRCUIT PROTECTION | EMC SHIELDING MATERIAL | CONNECTORS | SWITCHES | ASSEMBLY TECHNIQUE | POWER ELEMENTS

Important information: Würth Elektronik's design kits contain reference components. These components correspond with the current product development status on the day of supply. Exchange of the reference components to components with up-to-date product development status is not carried out automatically. No liability is taken for the use of these reference components. Therefore, please request new samples prior to releases for series production and product release.

Please check datasheets on www.we-online.com for specifications. Würth Elektronik eiSos GmbH & Co. KG, EMC & Inductive Solutions. © 2011

www.we-online.com

All products
in stock!