

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

....

www.mikroe.com

UVC Click





PID: MIKROE-4144

UVC Click is an ultraviolet sensing board which complements <u>UVC Light Click</u> for a ultimate ultraviolet solution. The board is based on <u>GUVC-T21GH</u> ultraviolet sensor from <u>GenUV</u>, capable of measuring UVC spectrum in the range of 220nm up to 280nm and light intensity from 0mW/cm² up to 9.3mW/cm². With high sensitivity and good solar blindness, it can be a perfect solution for monitoring sterilization lamps used in ultraviolet germicidal irradiation (UVGI), a disinfection method that is becoming an essential tool in the battle against viruses and bacteria. UVC Click has two ways of reading UV sensor output, direct analog output value and digital output thanks to MCP3221 ADC converter.

UVC Click board $^{\text{\tiny TM}}$ is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board $^{\text{\tiny TM}}$ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS $^{\text{\tiny TM}}$ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.









MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

Specifications

Туре	Optical,UVC Light
Applications	It can be used for UV measurement applications, sterilization lamp monitoring, prototyping of wearables, handsets, and various consumer electronics based on received UV light
On-board modules	GUVC-T21GH
Key Features	UVC sensing with 12-bit resolution, High Sensitivity, Good Solar Blindness
Interface	Analog,I2C
ClickID	No
Compatibility	mikroBUS™
Click board size	M (42.9 x 25.4 mm)
Input Voltage	3.3V or 5V

Resources

mikroBUS™

mikroSDK

Click board™ Catalog

Click Boards™


Downloads

UVC click schematic

UVC click example on Libstock

GUVC-T21GH datasheet

UVC click 2D and 3D files







health and safety management system.