

2201757

https://www.phoenixcontact.com/us/products/2201757

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

DIN rail bus adapter for ME and ME-MAX, design width: 17.5 mm, 5 parallel positions, color: light gray (similar to RAL 7035)



### Your advantages

· Space-saving DIN rail mounting

#### Commercial data

Item number	2201757
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	AC08
Product key	ACHACA
Catalog page	Page 39 (NTK-2014)
GTIN	4046356909037
Weight per piece (including packing)	3.636 g
Weight per piece (excluding packing)	3.636 g
Customs tariff number	85366990
Country of origin	DE



2201757

https://www.phoenixcontact.com/us/products/2201757

### Technical data

#### Product properties

Product type	DIN rail connector
Product family	TBUS5-17,5
Number of positions	5
Pitch	3.81 mm

#### **Dimensions**

Width	17.5 mm
Pitch	3.81 mm

#### Material specifications

Color	light grey
Flammability rating according to UL 94	V0
Insulating material	PA
Housing material	Polyamide



2201757

https://www.phoenixcontact.com/us/products/2201757

### **Approvals**

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2201757

cUL Recognized Approval ID: E118976-20151204				
	Nominal voltage	U <sub>N</sub> Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
	150 V	6 A	-	-

UL Recognized Approval ID: E118976-20151204					
		Nominal voltage U <sub>N</sub>	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
		150 V	8 A	-	-

cULus Recognized



2201757

https://www.phoenixcontact.com/us/products/2201757

### Classifications

UNSPSC 21.0

#### **ECLASS**

202.00			
	ECLASS-11.0	27460201	
	ECLASS-12.0	27460201	
	ECLASS-13.0	27460201	
ETIM			
	ETIM 9.0	EC002637	
UNSPSC			

39121400



2201757

https://www.phoenixcontact.com/us/products/2201757

### Environmental product compliance

EU RoHS				
Fulfills EU RoHS substance requirements	Yes, No exemptions			
China RoHS				
Environment friendly use period (EFUP)	EFUP-E			
	No hazardous substances above the limits			
EU REACH SVHC				
REACH candidate substance (CAS No.)	No substance above 0.1 wt%			



2201757

https://www.phoenixcontact.com/us/products/2201757

#### Accessories

IMC 1,5/5-ST-3,81 AU - Printed-circuit board connector

1943276

https://www.phoenixcontact.com/us/products/1943276



PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Gold, contact connection type: Pin, number of potentials: 5, number of rows: 1, number of positions: 5, number of connections: 5, product range: IMC 1,5/..-ST, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: without, mounting: without, type of packaging: packed in cardboard

#### IMC 1,5/5-ST-3,81 GY7035 AU - Printed-circuit board connector

1719707

https://www.phoenixcontact.com/us/products/1719707



PCB connector, nominal cross section: 1.5 mm², color: light grey, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Gold, contact connection type: Pin, number of potentials: 5, number of rows: 1, number of positions: 5, number of connections: 5, product range: IMC 1,5/..-ST, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: without, mounting: without, type of packaging: packed in cardboard

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com