



CORE DIMENSIONS		33T0231-10P			
UNCOATED CORE					
		MM	INCHES	MM	INCHES
OD	5.84	(.230)	±	0.15	(.006)
ID	3.05	(.120)	±	0.13	(.005)
TH	3.05	(.120)	±	0.13	(.005)
PARYLENE COATING					
OD	5.87	(.231)	±	0.15	(.006)
ID	3.02	(.119)	±	0.13	(.005)
TH	3.07	(.121)	±	0.13	(.005)

WEIGHT / K .64 LBS
 INITIAL PERMEABILITY 2700

ELECTRICAL SPECIFICATION								
	MIN (μH)	MIN TOL.	NOM (μH)	MAX (μH)	MAX TOL.	FREQ. (kHz)	VOLT. (V)	TURNS
L1	.857	(-20%)	1.071	1.285	(+20%)	100	≤ .00091	1
Q	62	-	-	-	-	100	≤ .00091	1

COATING SPECIFICATIONS			
TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
PARYLENE	(0.0127 / 0.5)	1000	0.30

NOTES:

- Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	Original Draft	1995/7/5	JBE
B	Added to Notes Database	2000/2/14	TPM
C	Changed from Star Print to -10P, Revised Template	2006/7/18	WMM
D	REVISED TEMPLATE	2019/3/10	Jcai

Date: 2019/3/10	DWG # 33T0231-10P-D	Rev:
Drawn By:: Jcai	Title # 33T0231-10P	D

Laird This document contains information which is proprietary to laird. No production or publication of this document in whole or in part shall be made without written authorization from Laird.