

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| APPLICABLE STANDARD | | | | | |
|--|--|---------------------------|---|--|----------------|
| RATING | OPERATING TEMPERATURE RANGE | Δ -40 °C TO 105 °C | STORAGE TEMPERATURE RANGE | -10 °C TO 50 °C (PACKED CONDITION) | |
| | VOLTAGE | 50 V AC / DC | OPERATING OR STORAGE HUMIDITY RANGE | RELATIVE HUMIDITY 90 % MAX (NOT DEWED) | |
| | CURRENT | 0.5 A (note) | APPLICABLE CABLE | t=0.3±0.05mm, GOLD PLATING | |
| SPECIFICATIONS | | | | | |
| ITEM | TEST METHOD | | REQUIREMENTS | QT | AT |
| CONSTRUCTION | | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | | X | X |
| Δ ELECTRICAL CHARACTERISTICS | | | | | |
| CONTACT RESISTANCE | AC 20 mV MAX (1 KHz) , 1 mA . | | 50 mΩ MAX. INCLUDING FPC,FPC BULK RESISTANCE (L=8mm) | X | X |
| INSULATION RESISTANCE | 100 V DC. | | 500 MΩ MIN. | X | X |
| VOLTAGE PROOF | 150 V AC FOR 1 min. | | NO FLASHOVER OR BREAKDOWN. | X | X |
| MECHANICAL CHARACTERISTICS | | | | | |
| MECHANICAL OPERATION | 20 TIMES INSERTIONS AND EXTRACTIONS. | | ① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | X | - |
| VIBRATION | FREQUENCY 10 TO 55 Hz, HALF AMPLITUDE 0.75 mm, - m/s ² FOR 10 CYCLES IN 3 AXIAL DIRECTIONS. | | ① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② CONTACT RESISTANCE: 50 mΩ MAX. | X | - |
| SHOCK | 981 m/s ² , DURATION OF PULSE 6 ms AT 3 TIMES IN 3 BOTH AXIAL DIRECTIONS. | | ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | X | - |
| FPC RETENTION FORCE | MEASURED BY APPLICABLE FPC. (THICKNESS OF FPC SHALL BE t=0.30mm AT INITIAL CONDITION.) | | DIRECTION OF INSERTION: 0.3N × n MIN. VERTICAL DIRECTION TO INSERTION: 0.2N × n MIN. (n:NUMBER OF CONTACTS) | X | - |
| ENVIRONMENTAL CHARACTERISTICS | | | | | |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE-40→+15To+35→+105→+15To+35°C TIME 30→ 2 TO 3 → 30→ 2 TO 3 min UNDER 5 CYCLES. | | ① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 50 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | X | - |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40±2°C, RELATIVE HUMIDITY 90 TO 95 %, 96 h. | | | X | - |
| DAMP HEAT,CYCLIC | EXPOSED AT -10 TO +65 °C, RELATIVE HUMIDITY 90 TO 96 %, 10 CYCLES,TOTAL 240 h. | | ① CONTACT RESISTANCE: 50 mΩ MAX. ② INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY) ③ INSULATION RESISTANCE: 50 MΩ MIN. (AT DRY) ④ NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | X | - |
| DRY HEAT | EXPOSED AT 105±2 °C, 96 h. | | ① CONTACT RESISTANCE: 50 mΩ MAX. | X | - |
| COLD | EXPOSED AT -40±3°C, 96 h. | | ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | X | - |
| CORROSION SALT MIST | EXPOSED AT 35±2°C , 5 % SALT WATER SPRAY FOR 96 h. | | ① CONTACT RESISTANCE: 50 mΩ MAX. ② NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR. | X | - |
| SULPHUR DIOXIDE [JIS C 60068-2-42] | EXPOSED AT 40±2 °C , RELATIVE HUMIDITY 80±5% ,25±5 ppm FOR 96 h. | | | X | - |
| HYDROGEN SULPHIDE [JIS C 60068-2-43] | EXPOSED AT 40±2 °C , RELATIVE HUMIDITY 80±5% ,10 TO 15 ppm FOR 96 h. | | | X | - |
| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
| Δ | 11 | DIS-F-00000943 | RT. IKEDA | HS. SAKAMOTO | 15. 12. 24 |
| REMARK | | | APPROVED | MO. ISHIDA | 09. 01. 21 |
| Δ | | | CHECKED | YN. TAKASHITA | 09. 01. 20 |
| | | | DESIGNED | HH. TSUKUMO | 09. 01. 20 |
| Unless otherwise specified, refer to IEC 60512. | | | DRAWN | HH. TSUKUMO | 09. 01. 20 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | | ELC4-159298-00 |
| HRS | SPECIFICATION SHEET | | PART NO. | FH40-**S-0. 5SV | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL580 | Δ 1/2 |

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|------------------------------|---|--|----|----|
| RESISTANCE TO SOLDERING HEAT | 1) REFLOW SOLDERING PEAK TMP. 250 °C MAX . REFLOW TMP. OVER 230 °C WITHIN 60 sec. 2) SOLDERING IRONS : TMP. 350±5°C FOR 5±1 sec . | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | x | — |
| SOLDERABILITY | SOLDERED AT SOLDER TEMPERATURE, 245±5 °C FOR IMMERSION DURATION, 2±0.5 sec. | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | x | — |

(note)

WHEN THE SAME VALUE OF CURRENT ARE APPLIED TO ALL CONTACTS AT THE SAME TIME IN ONCE, SET THE CURRENT TO THE 70 % OF THE RATED CURRENT VALUE.

| | | | | | |
|--|---------------------------|-------------|----------|-----------------|-------|
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | DRAWING NO. | | ELC4-159298-00 | |
| HRS | SPECIFICATION SHEET | | PART NO. | FH40-**S-0. 5SV | |
| | HIROSE ELECTRIC CO., LTD. | | CODE NO | CL580 | △ 2/2 |