

Part Number : 39532275

Series Number : 5597 Product Category : FFC / FPC Connectors

Documents & Resources

Drawings Drawing 039532275_sd.pdf

3D Models and Design Files 3D Model 039532275_stp.zip

Specifications Packaging Specification SPK-5597-001-001.pdf Product Specification PS-5597-004-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | (|
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS

- REACH SVHC

- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D

- Molex Product Compliance Declaration

Product Description : 1.25mm Pitch Easy-On FFC/FPC Connector, Through-Hole, Vertical, ZIF, 27 Circuits Status : Active Engineering Number : 5597-27CPB7F - IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | FFC / FPC Connectors |
| Series | 5597 |
| Description | 1.25mm Pitch Easy-On FFC/FPC Connector, Through-Hole, Vertical, ZIF, 27 Circuits |
| Product Family | Easy-On FFC FPC Connectors |
| Product Name | Easy-On |
| UPC | 822348190225 |

Agency

| UL E29179 |
|-----------|
|-----------|

Electrical

| Current - Maximum per Contact | 1.0A |
|-------------------------------|------|
| Voltage - Maximum | 200V |

Physical

| Actuator Type | Slider |
|--------------------------------|-----------------|
| Circuits (Loaded) | 27 |
| Circuits (maximum) | 27 |
| Color - Resin | Natural |
| Contact Position | N/A |
| Durability (mating cycles max) | 30 |
| Flammability | 94V-0 |
| Mated Height | 7.50mm |
| Material - Metal | Phosphor Bronze |
| Material - Plating Mating | Tin-Bismuth |
| Material - Plating Termination | Tin-Bismuth |

| Material - Resin | Polyester |
|-------------------------------|---------------|
| Net Weight | 2313.650/mg |
| Orientation | Vertical |
| Packaging Type | Tray |
| PC Tail Length | 3.50mm |
| PCB Locator | No |
| PCB Mounting | Through Hole |
| PCB Retention | None |
| Pitch - Mating Interface | 1.25mm |
| Plating min - Mating | 1.016µm |
| Plating min - Termination | 1.016µm |
| Polarized to PCB | No |
| Stackable | No |
| Temperature Range - Operating | -20° to +80°C |
| Wire/Cable Type | FFC/FPC |

This document was generated on Apr 15, 2024