

Part Number: 545481272

Product Description: 0.50mm Pitch Easy-On FFC/FPC Connector, 1.20mm Height, Right-Angle, Surface Mount, ZIF, Bottom Contact Style, 12 Circuits, Gold (Au) Plating

Series Number: 54548

Product Category: FFC / FPC Connectors

Status: Active

#### **Documents & Resources**

#### **Drawings**

Drawing 545481272\_sd.pdf

3D Models and Design Files 3D Model 545481272\_stp.zip

#### Specifications

SPK-54548-001-001.pdf

Product Specification 545480000-PS-001.pdf

### **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

# **Part Details**

### General

Status	Active
Category	FFC / FPC Connectors
Series	54548
Description	0.50mm Pitch Easy-On FFC/FPC Connector, 1.20mm Height, Right- Angle, Surface Mount, ZIF, Bottom Contact Style, 12 Circuits, Gold (Au) Plating
Comments	Black Actuator
Product Family	Easy-On FFC FPC Connectors
Product Name	Easy-On
UPC	196823012143

## Agency

UL	E29179
----	--------

## Electrical

Current - Maximum per Contact	0.5A
Voltage - Maximum	50V

# Physical

Actuator Type	Slider
Circuits (Loaded)	12
Color - Resin	Natural (White)
Contact Position	Bottom
Durability (mating cycles max)	20
Flammability	94V-0
Mated Height	1.20mm
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold

Material - Plating Termination	Tin
Material - Resin	Liquid Crystal Polymer
Net Weight	71.726/mg
Orientation	Right Angle
Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Mounting	Surface Mount
PCB Retention	Yes
Pitch - Mating Interface	0.50mm
Polarized to PCB	Yes
Stackable	No
Temperature Range - Operating	-20° to +85°C
Wire/Cable Type	FFC/FPC

## Mates With / Use With

### Mates with Part(s)

Description	Part Number
0.50mm Pitch Premo-Flex FFC Jumpers	<u>15020</u>
0.50mm Pitch Premo-Flex FFC Jumpers	<u>15120</u>

This document was generated on Apr 13, 2024