ATGBICS LC-LC OM3, Group Gear 35-0020LCLC Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 2m

Brand : ATGBICS Product code: 35-0020LCLC-C

Product name : LC-LC OM3, Group Gear 35-0020LCLC Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 2m

duct code: 35-0020LCLC-C

ATGBICS

LC-LC OM3, Group Gear 35-0020LCLC Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 2m

ATGBICS LC-LC OM3, Group Gear 35-0020LCLC Compatible Fibre Optic Cable, Multimode, Duplex, Aqua,

This product is high quality LC-LC (male to male) Fibre Patch Cable. LC connections allow higher density applications based on its smaller diameter. Being Multimode, it is typically used to connect 2 transceivers, more often over short reach applications. The OM3 cable has a core size of 50 microns and the diameter of the outer cladding is 125 microns. Our OM3 fibre patch cables are designed to maintain a low attenuation loss and speed stability. Our products are rigorously tested and we proudly offer a compatibility guarantee and lifetime warranty.

ATGBICS LC-LC OM3, Group Gear 35-0020LCLC Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 2m. Cable length: 2 m, Cable type: OFNR, Fibre optic type: OM3, Connector 1: LC, Connector 2: LC, Core diameter: 50 µm, Full duplex



Features		Features	
Cable length *	2 m	Insertion loss	0.2 dB
Fibre optic type	OM3	Return loss	50 dB
Connector 1 *	LC	Jacket material *	Polyvinyl chloride (PVC)
Connector 2 *	LC	Brand compatibility	Group Gear
Connector 1 gender *	Male	Country of origin	China
Connector 2 gender *	Male	Technical details	
Connector polish type	UPC OFNR Aqua colour	Sustainability certificates	RoHS
Cable type *		Doesn't contain	Halogen
Product colour *		Doesii t Contain	Halogeli
Full duplex	✓ Operational conditions		
Core diameter	50 μm	Operating temperature (T-T)	-40 - 70 °C
Cladding diameter	125 μm	Storage temperature (T-T)	-40 - 70 °C
Fiber mode structure	Multi-mode Weight & dimensions		
Wavelengths supported	850,1300 nm 10 Gigabit Ethernet, 40 Gigabit Ethernet, 100 Gigabit Ethernet	Cable diameter	2 mm
Ethernet interface type		Packaging data	
		Quantity per pack	1 pc(s)



5056468747501

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.