## ATGBICS LC-LC OM3, HPE AJ839A Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 50m

Brand : ATGBICS

Product code: AJ839A-C

Product name : LC-LC OM3, HPE AJ839A Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 50m

LC-LC OM3, HPE AJ839A Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 50m

ATGBICS LC-LC OM3, HPE AJ839A Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 50m:

This product is high quality LC-LC (male to male ) Fibre Patch Cable. LC connections allow higher density applications based on its smaller diameter. Being Multimode, it is typically used to connect 2 transceivers, more often over short reach applications. The OM3 cable has a core size of 50 microns and the diameter of the outer cladding is 125 microns. Our OM3 fibre patch cables are designed to maintain a low attenuation loss and speed stability. Our products are rigorously tested and we proudly offer a compatibility guarantee and lifetime warranty.

ATGBICS LC-LC OM3, HPE AJ839A Compatible Fibre Optic Cable, Multimode, Duplex, Aqua, 50m. Cable length: 50 m, Cable type: OFNR, Fibre optic type: OM3, Connector 1: LC, Connector 2: LC, Core diameter: 50 μm, Full duplex

## Features

Cable length *			
Fibre optic type			
Connector 1 *			
Connector 2 *			
Connector 1 gender *			
Connector 2 gender *			
Connector polish type			
Cable type *			
Product colour *			
Full duplex			
Core diameter			
Cladding diameter			
Fiber mode structure			
Wavelengths supported			


Ethernet interface type

50 m ОМЗ 1 C LC Male Male UPC OFNR Aqua colour 1 50 µm 125 µm Multi-mode 850,1300 nm 10 Gigabit Ethernet, 40 Gigabit Ethernet, 100 Gigabit Ethernet

ATGBICS	



Features			
Insertion loss	0.2 dB		
Return loss	50 dB		
Jacket material *	Polyvinyl chloride (PVC)		
Brand compatibility	HP		
Country of origin	China		
Technical details			
Sustainability certificates	RoHS		
Doesn't contain	Halogen		
Operational conditions			
Operating temperature (T-T)	-40 - 70 °C		
Storage temperature (T-T)	-40 - 70 °C		
Weight & dimensions			
Cable diameter	2 mm		
Packaging data			
Quantity per pack	1 pc(s)		



5056468737243

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.