

FOC-17P4-17P4-GL01/120 - Connecting cable



1087146

<https://www.phoenixcontact.com/us/products/1087146>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M17 series with preassembled FO plug assembly: 4-pos. plug-plug, multimode fiberglass G62. 5/125 µm OM1, with screw connection, length of FO cable: 120 m, IP67 degree of protection after being inserted, fixed installation in cable ducts, underground cable ducts, and cable protection pipes for indoor/outdoor use

Your advantages

- The connector is small and compact, and it has a maximum outer diameter of 21 mm, which enables high-density installation
- IP67 degree of protection, stainless steel housing, ambient temperature -40 °C ... +85 °C, suitable for industrial applications and harsh environments
- Armored fiber FO cable for indoor and outdoor applications, low smoke and free of halogen, standard length can be ordered from 10 m ... 200 m, customized length on request
- The connector has integrated protective cover, so that it can be used on site conveniently

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1087146 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | AB15 |
| Product key | ABNHBA |
| GTIN | 4055626883229 |
| Weight per piece (including packing) | 22.22 g |
| Weight per piece (excluding packing) | 22.22 g |
| Customs tariff number | 85447000 |
| Country of origin | CN |

FOC-17P4-17P4-GL01/120 - Connecting cable



1087146

<https://www.phoenixcontact.com/us/products/1087146>

Technical data

Product properties

| | |
|---------------------|-------------------------|
| Product type | Data cable preassembled |
| Number of positions | 4 |

Electrical properties

| | |
|---------------------|-----------------------|
| Transmission medium | Multi-mode fiberglass |
|---------------------|-----------------------|

Mechanical properties

| | |
|---------------------------------------|---------------|
| Tensile strength short-term/long-term | 1500 N / 800N |
|---------------------------------------|---------------|

Material specifications

| | |
|--|-------------------|
| Flammability rating according to UL 94 | V0 |
| Ferrule material | Zirconia ceramics |
| Outer sheath, material | LSZH |

Connector

Connection 1

| | |
|--------------|-----------------|
| Locking type | 17# thread type |
|--------------|-----------------|

Cable/line

| | |
|---|---|
| Cable length | 120 m |
| Cable weight | 40.00 kg/km |
| Cable type | Multimode fiberglass |
| Cable type | Non-metal armored fiber optic cable for indoor/outdoor applications |
| External cable diameter | 7.5 mm |
| Outer sheath, material | LSZH |
| External sheath, color | black |
| Smallest bending radius, fixed installation | 80 mm |
| Tensile strength short-term/long-term | 1500 N / 800N |
| Lateral pressure, long-term | 300.00 N/cm |
| Halogen-free | according to IEC 60754-1 |

FO cable

| | |
|---------------------|----------------------------------|
| Number of fibers | 4 |
| Fiber | 62.5/125 µm OM1 |
| Fiber type | Multimode fiberglass 62.5/125 µm |
| Attenuation | < 1.5 dB (1300 nm) |
| Transmission medium | Multi-mode fiberglass |

Environmental and real-life conditions

Ambient conditions

FOC-17P4-17P4-GL01/120 - Connecting cable



1087146

<https://www.phoenixcontact.com/us/products/1087146>

| | |
|---------------------------------|---------------------------------------|
| Degree of protection | IP65/IP67 |
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Shock | 50g, in accordance with IEC 61300-2-9 |

FOC-17P4-17P4-GL01/120 - Connecting cable



1087146

<https://www.phoenixcontact.com/us/products/1087146>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1087146>



EAC

Approval ID: 19060508

FOC-17P4-17P4-GL01/120 - Connecting cable



1087146

<https://www.phoenixcontact.com/us/products/1087146>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27061003 |
| ECLASS-12.0 | 27061003 |
| ECLASS-13.0 | 27061003 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002607 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

FOC-17P4-17P4-GL01/120 - Connecting cable



1087146

<https://www.phoenixcontact.com/us/products/1087146>

Environmental product compliance

| | |
|---|--|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

FOC-17P4-17P4-GL01/120 - Connecting cable



1087146

<https://www.phoenixcontact.com/us/products/1087146>

Accessories

FOC-FR19:1U-17S4-LCD2-OM1 - Patch panel

1087135

<https://www.phoenixcontact.com/us/products/1087135>

Preassembled 19" fiber-optic distributor box (1 RU) , M17 MPO series, for connecting an M17 MPO plug assembly.



FOC-FR19:1U-217S4-LCD4-OM1 - Patch panel

1087121

<https://www.phoenixcontact.com/us/products/1087121>

Preassembled 19" fiber-optic distributor box (1 RU) , M17 MPO series, for connecting an M17 MPO plug assembly.



FOC-17P4-17P4-GL01/120 - Connecting cable

1087146

<https://www.phoenixcontact.com/us/products/1087146>



FOC-17S4-LCD2-GF01/1 - Connecting cable

1087115

<https://www.phoenixcontact.com/us/products/1087115>

M17 series with preassembled FO socket assembly: 4-pos. M17 socket, LC duplex on the other end, 1 m long, multimode fiberglass G62.5/125 µm OM1, IP67 degree of protection after being inserted, fixed installation for indoor use



FOC-17S4-LCD2-GF01/2 - Connecting cable

1087114

<https://www.phoenixcontact.com/us/products/1087114>

M17 series with preassembled FO socket assembly: 4-pos. M17 socket, LC duplex on the other end, 2 m long, multimode fiberglass G62.5/125 µm OM1, IP67 degree of protection after being inserted, fixed installation for indoor use



FOC-17P4-17P4-GL01/120 - Connecting cable



1087146

<https://www.phoenixcontact.com/us/products/1087146>

FOC-17S4-ST:A4-GF01/1 - Connecting cable

1087108

<https://www.phoenixcontact.com/us/products/1087108>

M17 series with preassembled FO socket assembly: 4-pos. M17 socket, ST on the other end, 1 m long, multimode fiberglass G62.5/125 µm OM1, IP67 degree of protection after being inserted, fixed installation for indoor use



FOC-17S4-ST:A4-GF01/2 - Connecting cable

1087107

<https://www.phoenixcontact.com/us/products/1087107>

M17 series with preassembled FO socket assembly: 4-pos. M17 socket, ST on the other end, 2 m long, multimode fiberglass G62.5/125 µm OM1, IP67 degree of protection after being inserted, fixed installation for indoor use



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com