




400G Multimode 50/125 OM4 Fiber Optic Cable (Duplex SN-PC M/M), LSZH, Magenta, 1 m (3.3 ft.)

MODEL NUMBER: N823S-01M-MG



400 GbE Ethernet cable supports high bandwidths necessary for next-gen cloud services, hyperscale data centers and telecom carriers.

Features

400 GbE Cable Supports High Bandwidths for High-Density Data Networking

The N823S-01M-MG is a premium multimode fiber optic cable that supports 400 Gb Ethernet speeds for transmitting data and voice signals over short distances. As the amount of traffic in data networks grows, so does the need for next-generation devices and fiber cables to support much higher bandwidths in hyperscale, edge, enterprise and colocation data center interconnect (DCI) applications where density and speed are both very important.

Compact SN Connectors Designed for the Latest OSFP/QSFP-DD Transceivers

This 400 Gb cable features duplex SN connectors on both ends. SN connectors are four times smaller than standard LC connectors and provide individual and independent duplex fiber support for OSFP/QSFP-DD transceivers. Push/pull boots encourage dense vertical stacking within a crowded patch panel or switch and make the cable easy to install or remove with just one hand. The switchable SN/PC ends let you make quick polarity changes in the field without tools or the need to re-terminate the connectors.

Magenta-Colored Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The OM4-rated cable has a magenta jacket to identify it as multimode in a crowded patch panel or switch and prevent it from becoming accidentally disconnected. The round low-smoke zero-halogen (LSZH) jacket limits the amount of toxic smoke emitted in case of combustion, making it suitable for poorly ventilated areas.

Specifications

OVERVIEW	
UPC Code	037332274618
Technology	Multimode
Optical Mode	OM4
Mode Type	Multimode

Highlights

- Duplex SN connectors optimized for the latest 400 Gb OSFP/QSFP-DD transceivers
- Space-saving SN plugs are 4x smaller than standard LC for easier cable management
- Switchable connectors allow polarity conversion without tools or re-termination
- Compact push/pull boots allow easy installation/removal with just one hand
- Magenta LSZH jacket allows fast identification in a crowded switch or patch panel

Package Includes

N823S-01M-MG 400G Multimode 50/125 OM4 Fiber Cable, Magenta, 1 m (3.3 ft.)





CONNECTIONS		
Side A - Connector 1	SN DUPLEX (MALE)	
Side B - Connector 1	SN DUPLEX (MALE)	
Endface Polish	PC	
Switchable Polarity	Yes	
PHYSICAL		
Cable Jacket Color	Magenta	
Connector Color	Aqua; White	
Cable Jacket Material	LSZH	
Cable Jacket Rating	OFNR	
Cable Outer Diameter (OD)	1.60 mm	
Clad Diameter (microns)	125.0	
Core Diameter (microns)	50.0	
Primary Coating Diameter (microns)	245.0	
Number of Fibers	2	
Cable Length (ft.)	3.3	
Cable Length (m)	1.01	
Cable Length (in.)	39.4	
Minimum Bend Radius	20 mm (Dynamic); 10 mm (Static)	
Fiber Cable Length	1M (3.3 ft)	
ENVIRONMENTAL		
Operating Temperature Range	14° to 140°F (-10° to 60°C)	
Storage Temperature Range	14° to 140°F (-10° to 60°C)	
Operating Humidity Range	5% to 85% RH, Non-Condensing	
Storage Humidity Range	5% to 85% RH, Non-Condensing	
COMMUNICATIONS		
Network Compatibility	400 Gbps	
Wavelength	1300nm; 850nm	
Attenuation @ 850NM	3.5dB	
Attenuation @ 1300NM	1.5dB	
Insertion Loss	< 0.20 dB	
FEATURES & SPECIFICATIONS		
Push/Pull Tabs	No	





Breakout	No	
Trunk	No	
Optical Port	SN	
STANDARDS & COMPLIANCE		
Product Certifications	UL 1651	
Product Compliance	RoHS; CE (Europe); REACH	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.