ATGBICS AFCT-739ASMZ-EX5 Avago Broadcom Compatible Transceiver SFP+ 10GBase-LR (1310nm, SMF, 10km, DOM, Ext Temp)

Brand : ATGBICS **Product code:** AFCT-739ASMZ-EX5-C



Product name: AFCT-739ASMZ-EX5 Avago Broadcom Compatible Transceiver SFP+ 10GBase-LR (1310nm, SMF, 10km, DOM, Ext Temp)

AFCT-739ASMZ-EX5 Avago Broadcom Compatible Transceiver SFP+ 10GBase-LR (1310nm, SMF, 10km, DOM, Ext Temp)

ATGBICS AFCT-739ASMZ-EX5 Avago Broadcom Compatible Transceiver SFP+ 10GBase-LR (1310nm, SMF, 10km, DOM, Ext Temp):



ATGBICS AFCT-739ASMZ-EX5 SFP+ 10GBase-LR supports a distance of up to 10km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC connector. This product operates at temperatures between 0C to +85C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Avago Broadcom AFCT-739ASMZ-EX5= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

Performance		Features	
SFP transceiver type *	Fiber optic	Certification	CE, FCC, RoHS
Maximum data transfer rate * 10000 Mbit/s Interface type * SFP+ Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring 10000 Mbit/s SFP+ 10000 Mbit/s SFP+ 10000 Mbit/s 110000 Mbit/s	10000 Mbit/s	Power	
	× LC	Input voltage Maximum voltage Power consumption (typical) Operational conditions	3.3 V 3.5 V 1 W
	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	85 °C 0 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%	
(DDM) Wavelength-division multiplexing (WDM)	×	Weight & dimensions Width	13.4 mm
Features Product colour	Silver Metal	Depth Height Weight	56.5 mm 8.5 mm 20 g
Housing material Plug and Play		Packaging data	
Hot-Plug support Hot-swap ✓	*	Number of products included Package type	1 pc(s) Box
Easy to install	puntry of origin China	Technical details	
Country of origin Brand compatibility		Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead



5056468769534

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.