

WRXK9A Automatic Precision Cleaver

Automatic Rotating Blade & Auto-Bin

Introducing the WRXK9A precision cleaver with automatic blade rotation and automatic waste bin offering high precision fiber cleaving. Universal adapter plate accepts 250um, 900um, 2mm, and 3mm fiber cable and the WRXK9A is also compatible with industry standard removable fiber holders. Blade automatically rotates after each cleave, and can be used for 52,000 cleaves before needing to be replaced. Auto bin collects fiber waste automatically. Accurate cleave lengths range from 5 to 20 mm.



Features

- Precision cleaver with automatic blade rotation and automatic waste bin
- Stable operation with typical cleave angle 90 degrees +/- 0.5 degrees.
- Includes universal adapter plate for cleaving 250um, 900um, 2mm, and 3mm cable
- Compatible with industry standard fiber holders
- Sixteen blade positions for 52,000 cleaves
- Provides accurate cleave lengths from 5 to 20 mm
- Anvil opens high for clear visibility



Specifications

| Parameter | Value |
|---------------------|--------------------------------------|
| Applicable Fiber | 250um, 900um, 2mm, 3mm, single fiber |
| Fiber Cleave Length | 5mm - 16mm |
| Fiber Cleave Angle | 90 degrees +/- 0.5 degrees |
| Blade Life | 52000 cleaves |
| Holder | Universal fiber adapter plate |
| Weight/Dimensions | .75 lb / 4.1"(W) x 3.7"(D) x 1.9"(H) |

Ordering Information

| Part Number | Description |
|-------------|--|
| WRXK9A | Precision cleaver with automatic rotating blade and auto-bin |