



SENDUST TOROIDAL POWER INDUCTORS

FEATURES

- * Sendust Powdered Iron Toroidal Construction.
- * Optimized For Use as High Frequency DC Chokes.
- * Temp Rise Data: Ripple Currents $\leq 10\%$ @ 100KHz
- * Low Cost Self Lead Construction.
- * Lower AC Losses Than Normal Powdered iron

NOTES: Temp Rise T1 & T2 are calculated.

- 1) L_n = Nominal Ind. @ 0.0Adc
 L1 = Nominal Ind. @ I1 Adc, T1 Temp Rise
 L2 = Nominal Ind. @ I2 Adc, T2 Temp Rise
- 2) I1 Represents a 1-20% Drop in L_n
 I2 Represents a 20-40% Drop in L_n

ELECTRICAL SPECIFICATIONS AT 25°C - OPERATING TEMPERATURE RANGE -55°C TO +105°C

PART NUMBER	L _n (μH)	DCR (Ohm)	L1 (μH) @ I1 (dc A)	T1 (°C)	L2 (μH) @ I2 (dc A)	T2 (°C)	REF. DIMENSIONS IN INCHES						
							A	C	VT/B	HT/B	PIN OD		
VTK-01001	10	0.024	10	1	12	8	2	47	.31	.16	.14	.29	.014
VTK-02001	20	0.030	18	1	9	13	2	36	.38	.18	.16	.36	.016
VTK-05001	50	0.054	42	1	10	31	2	39	.48	.21	.19	.46	.016
VTK-10001	100	0.102	82	1	12	57	2	46	.59	.25	.23	.57	.016
VTK-15001	150	0.091	127	1	6	96	2	24	.76	.32	.30	.74	.020
VTK-25001	250	0.171	210	1	9	154	2	33	.92	.32	.30	.90	.018
VTK-01002	10	0.008	9	2	6	7	4	23	.51	.24	.21	.48	.025
VTK-02002	20	0.012	17	2	5	12	4	20	.63	.28	.25	.59	.032
VTK-05002	50	0.032	37	2	17	22	4	66	.60	.26	.24	.58	.0225
VTK-10002	100	0.043	79	2	9	53	4	33	.95	.34	.31	.92	.0285
VTK-15002	150	0.053	117	2	8	80	4	30	1.06	.40	.36	1.03	.0285
VTK-25002	250	0.053	205	2	5	150	4	21	1.24	.56	.52	1.20	.032
VTK-01005	10	0.005	9	5	6	7	10	22	1.00	.39	.33	.94	.051
VTK-02005	20	0.006	16	5	6	12	10	22	1.11	.45	.39	1.05	.051
VTK-05005	50	0.010	36	5	9	20	10	36	1.11	.45	.39	1.05	.051
VTK-10005	100	0.021	80	5	8	57	10	33	1.67	.57	.51	1.61	.051
VTK-15005	150	0.026	124	5	8	90	10	30	1.85	.75	.69	1.79	.050
VTK-20005	200	0.030	154	5	9	108	10	35	1.85	.75	.69	1.79	.051
VTK-30005	312	0.037	258	5	11	194	10	32	2.18	1.00	.84	2.10	.051
VTK-02007	20	0.004	18	7	5	13	14	19	1.32	.63	.56	1.24	.064
VTK-05007	50	0.010	41	7	8	29	14	29	1.70	.60	.53	1.63	.064
VTK-10007	100	0.013	78	7	8	54	14	30	1.88	.78	.70	1.80	.064
VTK-15007	150	0.020	128	7	7	96	14	28	2.18	.95	.86	2.10	.064
VTK-20007	200	0.025	168	7	8	120	14	32	2.18	.95	.86	2.10	.064
VTK-05010	50	0.006	40	10	7	33	16	18	1.91	.81	.72	1.82	.064
VTK-25010	250	0.027	167	10	26	122	16	50	2.19	1.10	.85	2.10	.057
VTK-07012	70	0.009	60	12	14	55	16	20	2.21	.98	.88	2.12	.080
VTK-01025	12	0.0023	9.4	25	26	8.7	30	32	2.25	.95	.75	1.85	.100

VTK FOR VERTICAL, HTK FOR HORIZONTAL



SENDUST TOROIDAL POWER INDUCTORS

FEATURES

- * Sendust Powdered Iron Toroidal Construction.
- * Optimized For Use as High Frequency DC Chokes.
- * Temp Rise Data: Ripple Currents $\leq 10\%$ @ 100KHz
- * Low Cost Self Lead Construction.
- * Lower AC Losses Than Normal Powdered iron

NOTES: Temp Rise T1 & T2 are calculated.

- 1) L_n = Nominal Ind. @ 0.0Adc
 L1 = Nominal Ind. @ I1 Adc, T1 Temp Rise
 L2 = Nominal Ind. @ I2 Adc, T2 Temp Rise
- 2) I1 Represents a 1-20% Drop in L_n
 I2 Represents a 20-40% Drop in L_n

ELECTRICAL SPECIFICATIONS AT 25°C - OPERATING TEMPERATURE RANGE -55°C TO +105°C

PART NUMBER	L _n (μH)	Rate IDC	DCR (Ohm)	L1 @ I1 T1			L2 @ I2 T2			REF. DIMENSIONS IN INCHES				
				(μH)	(dc A)	(°C)	(μH)	(dc A)	(°C)	A	C	VT/B	HT/B	PIN OD
VTK-00001	10	7.37	0.010	9.0	1.7	15	8.0	3.3	40	.31	.16	.14	.29	.036
VTK-00002	25	5.20	0.020	22.5	1.00	15	20.0	1.9	40	.38	.18	.16	.36	.032
VTK-00003	50	3.95	0.035	45.0	0.70	15	40.0	1.3	40	.48	.21	.19	.46	.028
VTK-00004	75	3.50	0.045	67.5	0.60	15	60.0	1.1	40	.59	.25	.23	.57	.025
VTK-00005	100	3.15	0.055	90.0	0.50	15	80.0	0.95	40	.76	.32	.30	.74	.025
VTK-00006	150	2.35	0.100	135.0	0.40	15	120.0	0.75	35	.92	.32	.30	.90	.020
VTK-00007	200	1.98	0.140	180.0	0.35	15	160.0	0.65	35	.51	.24	.21	.48	.018
VTK-00008	250	1.85	0.160	225.0	0.30	15	200	0.60	35	.63	.28	.25	.59	.018
VTK-00009	330	1.70	0.190	297.0	0.27	15	264	0.50	35	.60	.26	.24	.58	.018

VTK FOR VERTICAL, HTK FOR HORIZONTAL

Specifications subject to change without notice.

20381 BARENTS SEA CIRCLE, LAKE FOREST, CA 92630 • TEL: (949) 452-0511 • FAX: (949) 452-0512 • <http://www.premiermag.com>



SENDUST TOROIDAL POWER INDUCTORS

FEATURES

- * Sendust Powdered Iron Toroidal Construction.
- * Optimized For Use as High Frequency DC Chokes.
- * Low core loss
- * Low Cost Self Lead Construction.

NOTES:

- Ln = Nominal Ind. @ 0.0Adc
- L1 = Nominal Ind. @ I1 Adc, T1 Temp Rise
- Ln & L1 = +/-15%

ELECTRICAL SPECIFICATIONS AT 25°C - OPERATING TEMPERATURE RANGE -55°C TO +105°C

PART NUMBER	Ln (μH)	I1 (dc A)	L1 (μH)	T1 (°C)	DCR (Ohm)	REF. DIMENSIONS IN INCHES				
						A	C	VT/B	HT/B	PIN OD
XTK-00020	10	12.5	6.5	30	0.007	.95	.55	.46	.88	.053
XTK-00021	12	12.0	8.0	30	0.008	.95	.55	.46	.88	.053
XTK-00022	15	11.2	9.5	30	0.008	.95	.55	.46	.88	.053
XTK-00023	18	10.8	11.2	30	0.009	.95	.55	.46	.88	.053
XTK-00024	22	10.3	13.5	30	0.010	.95	.55	.46	.88	.053
XTK-00025	27	9.8	16.0	30	0.011	.95	.55	.46	.88	.053
XTK-00026	33	7.4	21.5	30	0.020	.95	.55	.45	.87	.042
XTK-00027	39	7.1	25.0	30	0.022	.95	.55	.45	.87	.042
XTK-00028	47	6.7	29.0	30	0.024	.95	.55	.45	.87	.042
XTK-00029	56	6.4	34.0	30	0.026	.95	.55	.45	.87	.042
XTK-00030	68	4.9	45.5	30	0.046	.95	.55	.44	.86	.034
XTK-00031	100	4.4	64.0	30	0.056	.95	.55	.44	.86	.034
XTK-00032	120	3.3	84.0	30	0.100	.95	.55	.44	.86	.027
XTK-00033	150	3.1	102.0	30	0.110	.95	.55	.44	.86	.027
XTK-00034	180	3.8	106.0	30	0.075	.95	.55	.48	.90	.034
XTK-00035	220	3.6	125.0	30	0.085	.95	.55	.48	.90	.034
XTK-00036	270	3.4	150.0	30	0.095	.95	.55	.48	.90	.034
XTK-00037	330	3.3	176.0	30	0.100	.95	.55	.48	.90	.034
XTK-00038	390	2.5	235.0	30	0.180	.95	.55	.46	.88	.027
XTK-00039	470	2.3	276.0	30	0.190	.95	.55	.46	.88	.027
XTK-00040	560	2.2	320.0	30	0.210	.95	.55	.46	.88	.027
XTK-00041	680	2.1	375.0	30	0.230	.95	.55	.49	.91	.027
XTK-00042	820	2.0	440.0	30	0.260	.95	.55	.49	.91	.027
XTK-00043	1000	1.9	520.0	30	0.280	.95	.55	.49	.91	.027
XTK-00044	1000	1.3	560.0	30	0.400	.86	.45	.37	.81	.022

VTK FOR VERTICAL, HTK FOR HORIZONTAL

SENDUST TOROIDAL POWER INDUCTORS


VTK-XXXX MECHANICAL

HTK-XXXX MECHANICAL



VTK-XXXXX OUTLINE
VERTICAL MOUNT

SCHEMATIC

HTK-XXXXX OUTLINE
HORIZONTAL MOUNT





HORIZONTAL OR VERTICAL MOUNT:
Table Part Numbers are Vertical Mount.
Change the "V" to "H" for Horizontal Mount.
Example:
VTK-05001 = Vertical Mount 50uH, 1.0Adc
HTK-05001 = Horizontal Mount 50uH, 1.0Adc



SCHEMATIC

APPLICATION



VARIATIONS AVAILABLE. FOR INTERMEDIATE VALUES AND/OR CUSTOM DESIGNS PLEASE CONSULT THE FACTORY.

Specifications subject to change without notice.

