


SMD Power Inductor CDRR73




Description

- Ferrite drum core construction.
- Magnetically shielded.
- L × W × H: 7.2 × 7.2 × 3.4 mm Max.
- Product weight: 0.6 g (Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.
- Qualification to AEC-Q200.

Dimension - [mm]



Land pattern and Schematics - [mm]



Environmental Data

- Operating temperature range: -40°C ~ +125°C (including coil's self temperature rise)
- Storage temperature range: -40°C ~ +125°C
- Solder reflow temperature: 260 °C peak.


Packaging

- Carrier tape and reel packaging
- 13.0" diameter reel
- 1500 pcs per reel

Applications

- For consumer electronics : HDD, personal computer, LCD display, etc.
- For automotive: ABS, SRS airbag, HID/LED, car audio, car navigation, LCD display, etc.

SMD Power Inductor CDRR73



Electrical Characteristics

Part No.	Inductance (μ H) [within] ※1	D.C.R. ($m\Omega$) [within] (at 25°C)	Saturation current (A) ※2 (at 20°C)	Temperature rise current (A) ※3
CDRR73NP-3R3MC	$3.3 \pm 20\%$	$23 \pm 20\%$	2.30	3.45
CDRR73NP-4R7MC	$4.7 \pm 20\%$	$30 \pm 20\%$	1.70	2.90
CDRR73NP-6R8MC	$6.8 \pm 20\%$	$41 \pm 20\%$	1.60	2.00
CDRR73NP-100MC	$10 \pm 20\%$	$53 \pm 20\%$	1.40	1.90
CDRR73NP-150MC	$15 \pm 20\%$	$75 \pm 20\%$	1.10	1.58
CDRR73NP-220MC	$22 \pm 20\%$	$110 \pm 20\%$	0.96	1.25
CDRR73NP-330MC	$33 \pm 20\%$	$160 \pm 20\%$	0.75	0.95
CDRR73NP-470MC	$47 \pm 20\%$	$240 \pm 20\%$	0.67	0.85
CDRR73NP-680MC	$68 \pm 20\%$	$310 \pm 20\%$	0.54	0.70
CDRR73NP-101MC	$100 \pm 20\%$	$450 \pm 20\%$	0.45	0.60
CDRR73NP-151MC	$150 \pm 20\%$	$650 \pm 20\%$	0.37	0.47
CDRR73NP-221MC	$220 \pm 20\%$	$1050 \pm 20\%$	0.29	0.37
CDRR73NP-331MC	$330 \pm 20\%$	$1670 \pm 20\%$	0.22	0.28
CDRR73NP-471MC	$470 \pm 20\%$	$2050 \pm 20\%$	0.20	0.26
CDRR73NP-681MC	$680 \pm 20\%$	$3150 \pm 20\%$	0.16	0.22
CDRR73NP-102MC	$1000 \pm 20\%$	$4780 \pm 20\%$	0.13	0.16

※1. Inductance measuring condition: at 100 kHz.

※2. Saturation current: The value of D.C. current when the inductance decreases to 90% of it's nominal value.













※3. Temperature rise current: The value of D.C. current when the temperature rise is $\Delta t = 40^\circ\text{C}$ ($T_a = 20^\circ\text{C}$).

SMD Power Inductor CDRR73



Saturation Current & Temperature Rise Graph

— L (20°C) — ΔT







SMD Power Inductor CDRR73





Saturation Current & Temperature Rise Graph

— L (20°C) — ΔT



Solder Reflow Condition



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong
Tel. +852-2880-6781
FAX. +852-2565-9600
sales@hk.sumida.com
Saitama(Japan)
Tel. +81-48-691-7300
FAX. +81-48-691-7340
sales@jp.sumida.com
Chicago
Tel. +1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai
Tel. +86-21-5836-3299
FAX. +86-21-5836-3266
shanghai.sales@cn.sumida.com
Seoul
Tel. +82-2-6237-0777
FAX. +82-2-6237-0778
sales@kr.sumida.com
Obernzell
Tel. +49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen
Tel. +86-755-8291-0228
FAX. +86-755-8291-0338
shenzhen.sales@cn.sumida.com
Singapore
Tel. +65-6296-3388
FAX. +65-6841-4426
sales@sg.sumida.com
Neumarkt
Tel. +49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei
Tel. +886-2-8751-2737
FAX. +886-2-8751-2738
sales@tw.sumida.com
San Jose
Tel. +1-408-321-9660
FAX. +1-408-321-9308
sales@us.sumida.com