

#### Sigma | Sigma SC

TE Internal #: 1624000-3

Radio Frequency Inductor, 10  $\mu$ H, 219 mA, 3.7  $\Omega$  DC Resistance, 10 %, Through Hole - Solder, Axial-Leaded, Ammo Packed, Length .

275 in [7 mm], Sigma SC

View on TE.com >



Passive Components > Inductors > High Frequency & RF Inductors



Inductor Type: Radio Frequency

Inductance: 10 µH

Current Rating (Max): 219 mA

DC Resistance:  $3.7 \Omega$ 

Inductor Quality Factor: 55

#### **Features**

## **Product Type Features**

Inductor Type	Radio Frequency
Element Type	Wire Wound
Electrical Characteristics	
Self Resonant Frequency	.05 GHz
Inductance	10 μΗ
Current Rating (Max)	219 mA
DC Resistance	3.7 Ω
Passive Component Tolerance	10 %
Body Features	

Lead Type	Axial-Leaded

## **Termination Features**

Termination Method to Printed Circuit Board	Through Hole - Solder	
---	-----------------------	--

#### **Dimensions**

Product Length	7 mm[.275 in]
Usage Conditions	

Operating Temperature Range	-55 - 100 °C



#### **Packaging Features**

Packaging Method	Ammo Packed
Other	
Inductor Quality Factor	55

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**















# Also in the Series | Sigma SC









# Customers Also Bought















### **Documents**

#### **CAD Files**

3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_1624000-3\_BA.2d\_dxf.zip

English

Radio Frequency Inductor, 10  $\mu$ H, 219 mA, 3.7  $\Omega$  DC Resistance, 10 %, Through Hole - Solder, Axial-Leaded, Ammo Packed, Length .275 in [7 mm], Sigma SC



**Customer View Model** 

ENG\_CVM\_CVM\_1624000-3\_BA.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1624000-3\_BA.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages

1309350\_PASSIVE\_COMPONENT

English

Axial Leaded Power Inductors - Type SC10, SC15, SC30 Series - Tyco Electronics Passives

English