# DMC-M 08-16 PN $\checkmark$ ACTIVE



#### **DEUTSCH**

TE Internal #: ZPF00000000015233

Rectangular Contact Inserts, Insert for Contacts, Pin, 8 Pole

Configuration, Crimp, Wire-to-Wire, 8 Position, Sealable, 20 – 16

AWG Wire Size

View on TE.com >



Connectors > Rectangular Connectors > Rectangular Contact Inserts



Rectangular Connector Insert Type: Insert for Contacts

Contact Type: Pin Pole Configuration: 8

Termination Method to Wire & Cable: Crimp

Connector System: Wire-to-Wire

### **Features**

### **Product Type Features**

Connector & Contact Terminates To	Wire & Cable
Rectangular Connector Insert Type	Insert for Contacts
Connector System	Wire-to-Wire
Sealable	Yes
Configuration Features	
Number of Positions	8
Body Features	
Primary Product Material	Composite
Contact Features	
Contact Type	Pin
Pole Configuration	8

# **Termination Features**

Contact Current Rating (Max)

Termination Method to Wire & Cable Crimp
--

13 A

#### **Mechanical Attachment**

Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

## **Housing Features**



Centerline (Pitch)	4.62 mm[.18 in]
Dimensions	
Wire Size	.61 – 1.21 mm²
Usage Conditions	
Operating Temperature Range	-55 – 175 °C[-67 – 347 °F]
Operation/Application	
Circuit Application	Power, Signal & High Speed Data
Packaging Features	
Packaging Quantity	1
Packaging Method	Package

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (1.2% in alloy) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Customers Also Bought





















# **Documents**

**Product Drawings** 

DMC-M 08-16 PN

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_ZPF00000000015233\_1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_ZPF00000000015233\_1.3d\_igs.zip

English

Rectangular Contact Inserts, Insert for Contacts, Pin, 8 Pole Configuration, Crimp, Wire-to-Wire, 8 Position, Sealable, 20 – 16 AWG Wire Size



**Customer View Model** 

ENG\_CVM\_CVM\_ZPF00000000015233\_1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

DMC-M Series Single Module EN4165

English