

YHV280-2PM-S-4MM-A

✓ ACTIVE

TE Internal #: YHV280-2PM-S-4MM-A
Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 2
Position, .409 in [10.4 mm] Centerline, Sealable, Orange, Signal
[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Housings



Connector System: **Wire-to-Board, Wire-to-Device**
Number of Positions: **2**
Connector & Housing Type: **Housing for Female Terminals**
Centerline (Pitch): **10.4 mm [.409 in]**
Sealable: **Yes**

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Device
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	2
Number of Rows	1

Electrical Characteristics

Operating Voltage	850 VDC
Nominal Voltage Architecture	12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V, 240 V, 500 V, 550 V, 600 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Orange
Connector & Keying Code	A

Contact Features

Contact Size	.63mm, 2.8mm
--------------	--------------



Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA GF
Centerline (Pitch)	10.4 mm[.409 in]

Dimensions

Connector Height	27.6 mm[1.087 in]
Product Width	55.3 mm[2.177 in]
Product Length	32.9 mm[1.295 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

Degree of Protection	IP6K9K
UL Flammability Rating	UL 94HB

Other

Serviceable	Yes
Connector Position Assurance Capable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------




EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2103124-1
HVA280 2P HEADER ASSY, KEY A



TE Part # YHVA280-2PHX-HDR-A
HVA280 2P (2103124-1) HEADER, KEY A

Customers Also Bought



TE Part # HDP24-24-91PN-P064
REC, 9P, BLK, N, NO JMP, 8/12/16, P



TE Part # 1587724-2
OUTER FERRULE, SIZE B, HVA280



TE Part # 3-1625890-4
2W SM M/OX 5% 270K



TE Part # 1-1718492-2
1.5MM TAB HSG 36 POS ASSY

YHV280-2PM-S-4MM-A

Housing for Female Terminals, Wire-to-Board / Wire-to-Device, 2 Position, .409 in [10.4 mm] Centerline, Sealable, Orange, Signal



TE Part # 2-2141600-2
TAB 2.8x0.8 CONTACT CF SRC Ag

TE Part # 4-2103015-5
PLUG SUBASSY, E, HVA280-2PHM F

TE Part # 4-2103015-4
PLUG SUBASSY, D, HVA280-2PHM F

TE Part # 4-2103015-6
PLUG SUBASSY, F, HVA280-2PHM F

TE Part # YHV280-2PM-S-4MM-B
HVA280-2PHM,SHUNTED,4SQMM, KEY B

TE Part # YHV280-2PM-S-4MM-E
HVA280-2phm,shunted,4sqmm,Key E

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_YHV280-2PM-S-4MM-A_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_YHV280-2PM-S-4MM-A_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_YHV280-2PM-S-4MM-A_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

HEMS Kit YHV280-2pm-s-4mm-A

English

Product Specifications

Application Specification

English