


# 391 Series

## TE5® Fast-Acting Fuse



### Description

The 391 Series are TE5® short circuit protector, fast-acting type, 65V rated fuses. For Short Circuit Protection of Sensitive Electronic Components and Assemblies.

### Features & Benefits

- Recognized to UL/CSA/NMX 248-1 and UL/CSA/NMX 248-14
- Reduced PCB space requirements
- Highly defined cut-off times
- Low internal resistance
- Flame resistant encapsulated casing
- RoHS-compliant and Lead-free
- Available from 0.125A to 4A.

### Additional Information



Resources



Accessories



Samples

### Applications

- Battery chargers
- Consumer Electronics
- Power supplies
- Industrial controllers

### Electrical Characteristics

| % of Ampere Rating | Opening Time           |
|--------------------|------------------------|
| 300                | 2 Seconds, <b>Max.</b> |

### Agency Approvals

| Agency | Agency File Number | Ampere Range |
|--------|--------------------|--------------|
| UL US  | E67006             | 0.125A - 4A  |
| UKCA   | NA                 | 0.125A - 4A  |

### Electrical Characteristics

| Amp Code | Rated Current | Marking Code* | Voltage Rating | Breaking Capacity | Nominal Cold Resistance (Ohms) | Cold Resistance $0.1 \times I_N$ max. (mΩ) | Power Dissipation $1.0 \times I_N$ max. (mW) | Melting Integral $10 \times I_N$ max. (A <sup>2</sup> s) | Agency Approvals |       |
|----------|---------------|---------------|----------------|-------------------|--------------------------------|--------------------------------------------|----------------------------------------------|----------------------------------------------------------|------------------|-------|
|          |               |               |                |                   |                                |                                            |                                              |                                                          | UKCA             | UL US |
| 0125     | 125 mA        | SP13          | 65 V           | 50A<br>@65VAC/VDC | 3.4000                         | 3400                                       | 190                                          | 0.006                                                    | x                | x     |
| 0160     | 160 mA        | SP16          | 65 V           |                   | 2.4800                         | 2450                                       | 210                                          | 0.011                                                    | x                | x     |
| 0200     | 200 mA        | SP20          | 65 V           |                   | 1.7500                         | 1750                                       | 240                                          | 0.020                                                    | x                | x     |
| 0250     | 250 mA        | SP25          | 65 V           |                   | 0.1950                         | 195                                        | 52                                           | 0.012                                                    | x                | x     |
| 0315     | 315 mA        | SP32          | 65 V           |                   | 0.1850                         | 155                                        | 65                                           | 0.018                                                    | x                | x     |
| 0400     | 400 mA        | SP40          | 65 V           |                   | 0.1200                         | 120                                        | 85                                           | 0.038                                                    | x                | x     |
| 0500     | 500 mA        | SP50          | 65 V           |                   | 0.0950                         | 95                                         | 105                                          | 0.063                                                    | x                | x     |
| 0630     | 630 mA        | SP63          | 65 V           |                   | 0.0750                         | 75                                         | 135                                          | 0.105                                                    | x                | x     |
| 0800     | 800 mA        | SP80          | 65 V           |                   | 0.0580                         | 58                                         | 170                                          | 0.170                                                    | x                | x     |
| 1100     | 1.00 A        | SP100         | 65 V           |                   | 0.0460                         | 46                                         | 220                                          | 0.280                                                    | x                | x     |
| 1125     | 1.25 A        | SP125         | 65 V           |                   | 0.0370                         | 37                                         | 270                                          | 0.450                                                    | x                | x     |
| 1160     | 1.60 A        | SP160         | 65 V           |                   | 0.0290                         | 29                                         | 350                                          | 0.832                                                    | x                | x     |
| 1200     | 2.00 A        | SP200         | 65 V           |                   | 0.0236                         | 23                                         | 440                                          | 1.060                                                    | x                | x     |
| 1250     | 2.50 A        | SP250         | 65 V           |                   | 0.0180                         | 18                                         | 550                                          | 2.219                                                    | x                | x     |
| 1315     | 3.15 A        | SP315         | 65 V           |                   | 0.0140                         | 14                                         | 700                                          | 3.870                                                    | x                | x     |
| 1400     | 4.00 A        | SP400         | 65 V           |                   | 0.0115                         | 12                                         | 900                                          | 6.500                                                    | x                | x     |


#### Notes:

- \* Physical Marking on top of the device.
- Resistance is measured at 10% of rated current, 25°C.

# 391 Series

## TE5® Fast-Acting Fuse


### Temperature Re-rating Curve




#### Note:

1. Derating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

### Average Time Current Curves



### Soldering Parameters - Wave Soldering



### Recommended Process Parameters:

| Wave Parameter                                       | Lead-Free Recommendation          |
|------------------------------------------------------|-----------------------------------|
| Preheat:<br>(Depends on Flux Activation Temperature) | (Typical Industry Recommendation) |
| Temperature Minimum:                                 | 100° C                            |
| Temperature Maximum:                                 | 150° C                            |
| Preheat Time:                                        | 60-180 seconds                    |
| Solder Pot Temperature:                              | 260° C Maximum                    |
| Solder Dwell Time:                                   | 2-5 seconds                       |

#### Recommended Hand-Solder Parameters:

Solder Iron Temperature: 350° C +/- 5° C  
Heating Time: 5 seconds max.

**Note:** These devices are not recommended for IR or Convection Reflow process.

# 391 Series


## TE5® Fast-Acting Fuse

### Product Characteristics

|                                  |                                                                                         |
|----------------------------------|-----------------------------------------------------------------------------------------|
| <b>Materials</b>                 | Base/Cap: Thermoplastic<br>Polyamide PA 6.6, UL 94V-0<br>Round Pins: Copper, Tin-plated |
| <b>Lead Pull Strength</b>        | 10 N (EN 60068-2-21)                                                                    |
| <b>Solderability</b>             | 260°C, ≤ 3s. (Wave)<br>350°C, ≤ 1s. (Soldering Iron)                                    |
| <b>Soldering Heat Resistance</b> | 260°C, 10s. (IEC 60068-2-20)<br>350°C, 3s. (Soldering Iron)                             |


|                              |                                                                                                                      |
|------------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>Operating Temperature</b> | -40°C to +125°C (consider re-rating)                                                                                 |
| <b>Climatic Category</b>     | -40°C to +85°C/21 days<br>(IEC 60068-1,-2-1,-2-2,-78)                                                                |
| <b>Stock Conditions</b>      | +10 °C to +60 °C RH,<br>≤ 75% yearly average, without dew, maximum<br>value for 30 days-95%                          |
| <b>Vibration Resistance</b>  | 24 cycles at 15 min. each<br>(IEC 60068-2-6)<br>10 - 60 Hz at 0.75 mm amplitude<br>60 - 2000 Hz at 10 g acceleration |

### Dimensions



Holes in the printed circuit board

### Part Numbering System



### Packaging

| Packaging Option  | Packaging Specification | Quantity | Quantity & Packaging Code | Taping Width |
|-------------------|-------------------------|----------|---------------------------|--------------|
| <b>391 Series</b> |                         |          |                           |              |
| Tape & Ammopack   | N/A                     | 1,400    | 0000                      | N/A          |

**Disclaimer Notice** - Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).