


USEQGSEACH4180

Aliases (USEQGSEACH4180)

KEMET, QGS, Gas Detection, SMD, Infrared, Small SMD Package, 12C Communication Compatible, High Dynamic Range



Click here for the 3D model.

Dimensions		
L	5.65mm NOM	
W	3.7mm NOM	
Т	1.55mm MAX	

Packaging Specifications				
Packaging	T&R, 178mm			
Packaging Quantity	800			
Typical Component Weight	70 ma			

General Information			
Series	QGS		
Туре	Gas Detection		
Style	SMD		
Description	12C		
Features	Small SMD Package, 12C Communication Compatible, High Dynamic Range		
RoHS	With Exemptions		
REACH	SVHC (PZT - CAS 12626-81-2)		
SCIP Number	bc4e3452-d0d0-4c97-93bd-778b4e41f2f2		
Qualifications	REACH		
MSL	3		

Specifications				
Temperature Range	-40/+85°C			
Power Supply Voltage	1.75 - 3.6 V			
Current	1 - 23 uA (Supply Current, Typical)			
D*	2.5 x 10^8 cm sqrt(Hz)/ W			
NEP	$2.7 \times 10^{-10} \text{ W/sqrt(Hz)}$			
Time Constant	10ms (10-20 Hz peak)			
Field of View	90 degrees			
Element Size	0.64mm x 0.64mm			
Filter	3.3um, BW: 160nm, Gas: CH4			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.