ASSOCIATION ELECTRONICS	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions. This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assemble level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsition.						nbly with lower ponsibility.							
1752-21.1 IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x				lard	Form Type Distribute	Form Type * Declaration Class * Distribute Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information						1		
Supplier	Information													
Company	name*		Company unique ID				Unique ID Authority				Response Date*			
onsemi	onsemi										2024-04-15			
Contact Name			Title - Conta	Title - Contact			Phone - Contact*				Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
Authorized	d Representative*		Title - Repre	Title - Representative			Phone - Representative*				Email - Representative*			
Product-E	Product-Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
	Requester Item Number Mfr Item		Number Mfr Item Name			·	Effective Date	Version	Manufacturing Site		Weight*	UOM	Unit Type	
NC7WZ3		38L8X Dual 2-Inp NAND O/D		D O/D		2024-04-15		ТНВ		3.4466	mg	Each		
Manufac	Manufacturing Process Information													
Terminal Plating / Grid Array Material			Terminal Base Alloy J-STD-020		J-STD-020 MS	L Rating	Peak Process Body Temperature Max Time a		ature Max Time at Peal	eak Temperature Number of Reflow Cycles				
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		1		260	С	30	seconds 3				
Comments														
level 1 - maximum time at peak temperature during soldering is 10-30 seconds														
For more information regarding material composition please refer to page 3														

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier have provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recurined by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.1476	mg	Supplier	Silicon (Si)	7440-21-3		0.1476	mg
Die Attach Tape	0.0154	mg	Supplier	Acrylic AE Copolymer	58152-79-7		0.0023	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.0077	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.0022	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.0011	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0022	mg
Lead Frame	1.0344	mg	Supplier	Magnesium (Mg)	7439-95-4		0.0018	mg
			Supplier	Silicon (Si)	7440-21-3		0.0077	mg
			В	Nickel (Ni)	7440-02-0		0.0336	mg
			Supplier	Copper (Cu)	7440-50-8		0.9914	mg
Mold Compound-Black	2.225	mg	Supplier	Epoxy resins	129915-35-1		0.1112	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.1112	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0089	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.0512	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		1.8913	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0512	mg
Plating	0.0146	mg	Supplier	Palladium (Pd)	7440-05-3		0.0011	mg
			В	Nickel (Ni)	7440-02-0		0.0133	mg
			Supplier	Gold (Au)	7440-57-5		0.0002	mg
Wire Bond	0.0096	mg	Supplier	Palladium (Pd)	7440-05-3		0.0002	mg
			Supplier	Gold (Au)	7440-57-5		0	mg
			Supplier	Copper (Cu)	7440-50-8		0.0094	mg