



Powering Business Worldwide

## Eaton Cybersecure Gigabit Industrial Gateway Card for UPS and PDU, UL 2900-1 and IEC 62443-4-2 Certified

MODEL NUMBER: INDGW-M2



Improves power system reliability by warning IT administrators of pending issues and helping to perform safe shutdowns of servers and storage.

### Features

#### UPS Connectivity Device Certified to Strict UL Cybersecurity Standards

The INDGW-M2 Gigabit Industrial Gateway Mini-Slot card meets both UL 2900-1 and IEC 62443-4-2 cybersecurity standards, empowering IT professionals with superior Gigabit speed, capabilities and features, while ensuring the highest level of defense against emerging cybersecurity threats. Security enhancements include strong encryption, configurable password policy and usage of CA and PKI signed certificates. This network interface is recommended for use with better performing, cost-effective and widely deployed Gigabit network switches.

#### Compatible with Eaton Intelligent Power Manager

INDGW-M2 works with IPM v1.61 and higher to improve business continuity by triggering policies configured to keep mission-critical applications running in case of power or environmental anomalies, including virtual machine relocation or automated disaster recovery action.

#### Enables Remote UPS Management

INDGW-M2 combines the features of an SNMP agent, HTTP/web server and Modbus card to facilitate remote monitoring of your UPS system. It enables remote management of a UPS through load shedding and safe shutdowns and reboots protected devices attached to load segments. It monitors site electrical data, UPS self-test logs, alert logs and logged power events like blackouts, brownouts and overvoltage conditions. You can receive alert notifications via email or SMS. Real-time clock links to a Network Time Protocol (NTP) server to maintain current day and date even after a UPS shutdown.

#### Supports Multiple Protocols

This network interface provides versatile support through IPv4, IPv6, HTTPS, TLS 1.2, SNMPv1, SNMPv3, NTP, TFTP, SMTP, SMTPS, BOOTP, DHCP, SLAAC, SSH, MQTTS, Modbus TCP, Modbus RTU, BACnet IP and BACnet BBMD. It also supports Google Chrome and Mozilla Firefox web browsers. DHCP/Manual configuration support enables automatic or manual assignment of network settings.

#### Optional Sensor Monitors Environmental Conditions

The EMPDT1H1C2 Environmental Monitoring Probe (EMP) Gen 2 (sold separately) provides remote temperature and humidity monitoring, as well as a dry contact interface to monitor alarm, security and telecom devices. You can daisy-chain up to three EMPDT1H1C2 probes to a host, allowing multiple sensor connections. The probe is compatible with INDGW-M2 and Eaton rack PDUs, including G3

### Highlights

- Meets stringent UL 2900-1 and IEC 62443-4-2 cybersecurity standards
- Enhancements include strong encryption and configurable password policy
- Fast 1 Gbps speeds compatible with widely deployed Gigabit network switches
- Enables remote UPS management by turning them into managed devices
- Compatible with optional EMPDT1H1C2 environmental monitoring module

### System Requirements

Eaton UPS system with compatible accessory slot, including 5P, 5PX, 5PX G2, 9130, 9PX, 9PXM, 9SX, 93PM and 93E

### Package Includes

- Gigabit Industrial Gateway Mini-Slot Card
- USB configuration cable, 5 ft. (1.5 m)
- User's Guide



Powering Business Worldwide

(firmware 4.x or later), G3HD and G3+ models.

## Specifications

| OVERVIEW                           |   |
|------------------------------------|---|
| UPC Code                           | 743172101884  |
| INPUT                              |   |
| Nominal Input Voltage(s) Supported | 12V DC; 5V DC; 9V DC  |
| CONNECTIONS                        |   |
| Slot Type                          | Mini-slot   |
| PHYSICAL                           |   |
| Unit Dimensions (hwd / in.)        | 1.700 x 5.200 x 2.600   |
| Unit Dimensions (hwd / mm)         | 132.08 x 66.04 x 43.18  |
| Unit Weight (lbs.)                 | 0.156   |
| Unit Weight (kg)                   | 0.07  |
| ENVIRONMENTAL                      |   |
| Operating Temperature Range        | 32° to 104°F (0° to 40°C)   |
| Operating Humidity Range           | 90% RH max. without condensation  |
| COMMUNICATIONS                     |   |
| Network Compatibility              | 1 Gbps (Gigabit)  |
| Protocol Support                   | HTTPS, TLS 1.2, SNMPv1, SNMPv3, NTP, TFTP, SMTP, SMTPS, BOOTP, DHCP, SLAAC, SSH, MQTTS, ModbusTCP, Modbus RTU, BACnet IP, BACnet BBMD |
| STANDARDS & COMPLIANCE             |   |
| Product Compliance                 | CE (Europe); RoHS3  |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.