



TECHNICAL

AGENCY APPROVAL:	cULus
RATED SUPPLY VOLTAGE:	120VAC
RATED CURRENT:	UP TO 15 AMPS
RESET TYPE:	MANUAL
OPERATING FREQUENCY:	60 Hz
TYPE:	CLASS A
GROUND TRIP CURRENT:	4-6 mA
OVERLOAD CURRENT:	90 AMP
INSULATION VOLTAGE:	1,500 VRMS - 1 MINUTE
ENDURANCE OPERATIONS:	3,000 OPERATIONS

MATERIAL NUMBER	ENGINEERING NUMBER	LENGTH "A"	LENGTH "L"
1301530028	15050-3TT	1 FT.	2 FT. ± 1 IN.
1301530039	15050-6TT	5 FT.	6 FT. ± 2 IN.
1301530025	15050-25TT	24 FT.	25 FT. ± 2 IN.
1301530033	15050-50TT	49 FT.	50 FT. ± 2 IN.

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION															
<div><div><div><div><div></div></div></div><div><div></div></div></div><div>= 0</div></div> <div><div><div><div><div></div></div></div><div><div></div></div></div><div>= 0</div></div> <div><div><div><div><div></div></div></div><div><div></div></div></div><div>= 0</div></div>	DIMENSION UNITS		SCALE		CURRENT REV DESC: UPDATED PLUG DIMENSION.			<div>molex</div>								
	INCH		NTS													
	GENERAL TOLERANCES (UNLESS SPECIFIED)							EC NO: 730358 DRWN: PPURSUTANDEL 2022/11/29 CHK'D: DNGUYEN62 2023/02/17 APPR: HKNEELAND 2023/02/21			GFCI IN-LINE 15A WITH MOLDED PLUG & TRI-TAP					
ANGULAR TOL		±	°													
4 PLACES		±		PRODUCT CUSTOMER DRAWING												
3 PLACES		±					DOCUMENT NUMBER				DOC TYPE	DOC PART	REVISION			
2 PLACES		±					1301530028				PSD	000	B			
1 PLACE		±														
0 PLACES		±		INITIAL REVISION:		DRWN: PPURSUTANDEL 2021/12/27		2022/01/21								
DIVISIONAL SYMBOLS	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
							C-SIZE		130153		SEE TABLE		GENERAL MARKET		1 OF 1	