

Item Number

**IDH Number** 

HD3561-B30 397720

<u>Product Description</u> LOCTITE STYCAST HD 3561 known as HYSOL HD3561

QT



Revision Number: 004.1 Issue date: 07/09/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

LOCTITE STYCAST HD 3561 known as IDH number: **HYSOL HD3561 QT** 

397720

Product type:

Epoxy Hardener

Item number: Region:

HD3561-B30

Restriction of Use: Company address: None identified

Contact information:

**United States** 

Henkel Corporation One Henkel Wav

Telephone: +1 (860) 571-5100

Rocky Hill, Connecticut 06067

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER:

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1



#### **Precautionary Statements**

Prevention:

Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves, clothing, eye and face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off

immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash

contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 397720 Product name: LOCTITE STYCAST HD 3561 known as HYSOL HD3561 QT Page 1 of 5

Hazardous Component(s)	CAS Number	Percentage*
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	90 - 100

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products: Oxides of carbon, oxides of nitrogen, irritating organic vapors. Ammonia.

Collect contaminated fire extinguishing water separately. This must not be

discharged into drains.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Isolate area. Keep unnecessary personnel

away. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to

clean up.

## 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do

not taste or swallow. Refer to Section 8.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use. Do not store in reactive metal

containers.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-

rubber gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:ColorlessOdor:AmmoniacalOdor threshold:Not available.

pH: Alkaline

Vapor pressure:3.00 mm hg (21 °C (69.8 °F))Boiling point/range:294.8 °C (562.6 °F)Estimated

Melting point/ range: Not available.

Specific gravity: 1.01 at 21 °C (69.8 °F)

Vapor density: 27.8481

Flash point: 121 °C (249.8 °F) Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: 260 °C (500°F) Flammability: Not applicable **Evaporation rate:** Not available. Solubility in water: Completely soluble Partition coefficient (n-octanol/water): Not available.

VOC content:
Vocantent:
Vocantent

#### 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition Oxides of

products:

Oxides of carbon. Oxides of nitrogen. Ammonia. Irritating vapors. Nitrogen oxide can react

with water vapor to form corrosive nitric acid.

Incompatible materials: Acids. Oxidizing agents. Peroxides. Sodium hypochlorite. This product slowly corrodes copper,

aluminum, zinc and galvanized surfaces.

Reactivity: Not available.

Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition. Store away from

incompatible materials.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:

Severe respiratory tract irritation.

Skin contact:

Causes skin burns. May cause allergic skin reaction.

Eye contact: Ingestion:

Causes serious eye damage. Burns of the eye may cause blindness. Irritation and corrosive action can occur in the mouth, stomach tissue and digestive tract if

swallowed. Danger of perforation of the esophagus and the stomach.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
3.3'-Oxybis(ethyleneoxy)bis(propylamine)	None	Corrosive

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No	

## **ECOLOGICAL INFORMATION**

**Ecological information:** 

Not available.

# DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

D002: Corrosive.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Amines, liquid, corrosive, n.o.s. (Diethylene glycol di-(3-aminopropyl) ether)

Hazard class or division:

**UN 2735** 

Identification number: Packing group:

Ш

International Air Transportation (ICAO/IATA)

Proper shipping name:

Amines, liquid, corrosive, n.o.s. (Diethylene glycol di-(3-aminopropyl) ether)

Hazard class or division:

Identification number:

**UN 2735** 

Packing group:

Ш

Water Transportation (IMO/IMDG)

Proper shipping name:

AMINES, LIQUID, CORROSIVE, N.O.S. (Diethylene glycol di-(3-aminopropyl)

ether)

Hazard class or division: Identification number:

UN 2735

Packing group:

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS:

None above reporting de minimis.

CERCLA/SARA Section 311/312:

Immediate Health

CERCLA/SARA Section 313:

None above reporting de minimis.

California Proposition 65:

No California Proposition 65 listed chemicals are known to be present.

#### **Canada Regulatory Information**

**CEPA DSL/NDSL Status:** 

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 16

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

07/09/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

	4	