

ELBA SILICONE LUBRICATING GREASE 1208-ES

Elba 1208-ES is lubricating grease designed for adaptability in a wide range of applications where contacting surfaces are under heavy load and where high temperatures are expected.

Elba 1208-ES is useful as corrosion inhibitor, water repellent, mold release, and metal, rubber and plastic parts lubricant.

Elba 1208-ES features no separation at temperatures up to 500°F, low volatility, non-corrosive, plus ensures performance, consistency and stability.

Data	Typical Values
Appearance	White
Temperature	-100°F to 500°F
Worked Penetration	260
Unworked Penetration (200 – 250 range)	230
Bleed	Stable @ 500°F
Evaporation (< 1% @ 500°F)	0.30% @ 500°F
Specific Gravity	1.01 -1.03
Hegman Grind (Mils)	1.5

Key Features:	Application:	Containers:
Low Volatiles	Fire Extinguisher	400 lb Drum
Excellent Dispersion	Valves	40 lb Plastic Pail
Wide Temperature Range	Fraction HP Motors	8 lb. Plastic Pail
Non Corrosive	Home Appliance	8 lb. Plastic Pail
Does Not Separate	Lubricant	1 lb Jar
Chemical & Thermal Resistant	Plug Valves	14.1 oz Cartridge
Water Repellent	Electrical	5.3 oz Plastic Tube

