

TECHNICAL

ENCLOSURE:

AGENCY APPROVAL: cULus
RATED SUPPLY VOLTAGE: 120 VAC

RATED CURRENT: UP TO 20 AMPS

RESET TYPE: MANUAL
OPERATING FREQUENCY: 60 Hz
TYPE: CLASS A
GROUND TRIP CURRENT: 5mA +/- 1mA

DOCUMENT STATUS P1 RELEASE DATE 2022/12/13 21:50:37

OVERLOAD CURRENT: 120 AMPS, 50% INDUCTIVE INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE ENDURANCE OPERATIONS: 3000 OPERATIONS

3000 OPERATIONS TYPE 4X, IP69, IP69K

10

	· L				ORMATION THAT IS PROPRIE	ETARY TO N	MOLEX	ELECTRONIC TEC	CHNOLOGIES, LLC AND S	HOULD NOT BE	USED WIT	THOUT WR	ITTEN PER	RMISSION	
SYMBOL	S	DIMENSION UNITS	SCAL	Ξ	CURRENT REV DESC: S	SALES DR	G RELEASED.								
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	ן כ	INCH	NT	S						no	le	X			
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	o	GENERAL TOLERANCES (UNLESS SPECIFIED)						-	_						
F/= (- 1	ANGULAR TOL ± °			EC NO: 723814				INLINE GFCI 20A, 120\ W/ 27W47(3) AND 26W47 WA						
		4 PLACES	±		DRWN: VBASUTHKA	RP		2022/08/23	VVI ZI VV41 (3) AND ZOVV41 VVAILATTE						
DIVISION	AL	3 PLACES ±			CHK'D: DNGUYEN62			2022/12/06	-						
SYMBOL	- 1	2 PLACES	± ±		APPR: WLEUNG 2			2022/12/13	PRODUCT CUSTOMER DRAWING						
	┝				INITIAL REVISION:				DOCUMENT NUMBER			DOC TYPE	DOC PART	REVISION	
		1 PLACE			DRWN: A.L.			2007/24/01	12015		DOD				
		0 PLACES	±		APPR:			13015	30135		PSD	000	A		
		DRAFT WHERE APPLICABLE		.E	THIRD ANGLE PROJECTION DRAWING		NG	SERIES	MATERIAL NUMBER CUSTOMER		SHEET NUMBER				
		MUST REMAIN WITHIN DIMENSIONS				C-SIZ	ZE	130153	1301530135	GENER	AL MA	RKET	1 OF 1		
	5				4			3	2		1				