

	1	2	3	4	5	6	7																																																																						
A	③ 500.50 4.60 2.00±0.10 2.00±0.10 2.00xNo. of Positions±0.40 2.00xNo. of Contacts/2-2.00±0.20 2.00±0.15 0.89 2.00 2.70 5.40 0.45±0.10 0.35±0.05 19° 0.50 2.50±0.25 4.50 2.80 4.00±0.20 4.40±0.25 0.12 Detail A(3:1) ENVIRONMENTAL 1.Operation Temperature: Gold plating: -55°C to +105°C Tin plating: -40°C to +105°C 2.Soldering Temperature: +260°C 10s max. 3.Mechanical life cycle: min.200 ④ Order code A-SL200-EG-xxxMR1:Tape reel+Cap:1*2P~1*25P A-SL200-EG-xxxMP1:Tube+Cap:1*5P~1*40P Contact Plating G-Gold flash Z-Tin No. of Contacts							F																																																																					
B								B																																																																					
C								C																																																																					
D								D																																																																					
E								E																																																																					
F								F																																																																					
G	RoHS compliant Unit:mm <table><tr><th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th colspan="2">TOLERANCE</th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><td>X.X</td><td>±0.30</td><td></td><td></td><td></td><td>Drawn</td><td>24.11.2008</td><td>N.Schulz</td></tr><tr><td>X.XX</td><td>±0.20</td><td>④</td><td>Update the packing</td><td>08.04.2015</td><td>Winnie</td><td>Approved</td><td>08.04.2015</td><td>Winnie</td></tr><tr><td>X.XXX</td><td>±0.10</td><td>③</td><td>Update</td><td>29.05.2013</td><td>Amy</td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td>②</td><td>Update</td><td>28.08.2009</td><td>Dean</td><td></td><td></td><td></td></tr><tr><td>X°</td><td>±5°</td><td>①</td><td>Drawn</td><td>24.11.2008</td><td>N.Schulz</td><td></td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td><td></td><td></td></tr></table> ASSMANN WSW/ components Customer-No. ASSMANN WSW-No. A-SL200-EG-xxxMX1 Drawing-No. ASS 2892 CO rev04 Replace SHEET							Scale	Free							TOLERANCE								X.X	±0.30				Drawn	24.11.2008	N.Schulz	X.XX	±0.20	④	Update the packing	08.04.2015	Winnie	Approved	08.04.2015	Winnie	X.XXX	±0.10	③	Update	29.05.2013	Amy				DIM	TOL	②	Update	28.08.2009	Dean				X°	±5°	①	Drawn	24.11.2008	N.Schulz				Angle	TOL	Id.	Modification	Date	Name				G
Scale	Free																																																																												
TOLERANCE																																																																													
X.X	±0.30				Drawn	24.11.2008	N.Schulz																																																																						
X.XX	±0.20	④	Update the packing	08.04.2015	Winnie	Approved	08.04.2015	Winnie																																																																					
X.XXX	±0.10	③	Update	29.05.2013	Amy																																																																								
DIM	TOL	②	Update	28.08.2009	Dean																																																																								
X°	±5°	①	Drawn	24.11.2008	N.Schulz																																																																								
Angle	TOL	Id.	Modification	Date	Name																																																																								
H								H																																																																					
	1	2	3	4	5	6	7																																																																						