

Part Number: 5018761040

Product Description: 2.00mm Pitch, iGrid PCB Header, Dual Row, Right-Angle, Through Hole,

Matte Tin (Sn) Plating, Positive Lock, 10 Circuits, Tray, 3.20mm PC Tail Length, Natural

Status: Active

Series Number: 501876

**Product Category: PCB Headers and** 

Receptacles

#### **Documents & Resources**

#### Drawings

Drawing 5018761040\_sd.pdf

#### 3D Models and Design Files

2D Drawing DXF 5018761040.dxf

2D Drawing DXF (PDF) 5018761040.pdf

3D Model 5018761040\_stp.zip

#### **Specifications**

Application Specification 5016460000-A00.pdf
Application Specification 5016460000-A01.pdf
Packaging Specification SPK-501876-001-001.pdf
Product Specification 5016461001-PS-001.pdf
Product Specification PS-501646-001-001.pdf

# **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Compliant with Exemption 44; 33                |
|--------------------|--|
| China RoHS         | <b>©</b>                                       |
| EU ELV             | Not Relevant                                   |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21         |
| REACH SVHC         | Not Contained per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                      |

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC

## - Low-Halogen

# Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

# **Part Details**

## General

| Status         | Active  |
|----------------|---|
| Category       | PCB Headers and Receptacles   |
| Series         | 501876  |
| Description    | 2.00mm Pitch, iGrid PCB Header,<br>Dual Row, Right-Angle, Through<br>Hole, Matte Tin (Sn) Plating,<br>Positive Lock, 10 Circuits, Tray,<br>3.20mm PC Tail Length, Natural |
| Application    | Signal, Wire-to-Board   |
| Component Type | PCB Header  |
| Product Family | iGrid Wire-to-Board Dual-Row<br>System  |
| Product Name   | iGrid   |
| UPC            | 822350170871  |

## Agency

| CSA | LR19980 |
|-----|---------|
| UL  | E29179  |

## **Electrical**

| Current - Maximum per Contact | 2.0A             |
|-------------------------------|------------------|
| Voltage - Maximum             | 250V AC (RMS)/DC |

# **Physical**

| Breakaway         | No |
|-------------------|----|
| Circuits (Loaded) | 10 |

| <b>5</b> 1 1 1 1 1             |                |
|--------------------------------|----------------|
| Circuits (maximum)             | 10             |
| Color - Resin                  | Natural        |
| Durability (mating cycles max) | 30             |
| Flammability                   | 94V-0          |
| Glow-Wire Capable              | No             |
| Keying to Mating Part          | Yes            |
| Lock to Mating Part            | Yes            |
| Material - Metal               | Brass          |
| Material - Plating Mating      | Matte Tin      |
| Material - Plating Termination | Matte Tin      |
| Material - Resin               | Polyamide      |
| Net Weight                     | 965.000/mg     |
| Number of Rows                 | 2              |
| Orientation                    | Right Angle    |
| Packaging Type                 | Tray           |
| PC Tail Length                 | 3.20mm         |
| PCB Locator                    | No             |
| PCB Retention                  | None           |
| PCB Thickness - Recommended    | 1.20mm, 1.60mm |
| Pitch - Mating Interface       | 2.00mm         |
| Polarized to Mating Part       | Yes            |
| Polarized to PCB               | No             |
| Stackable                      | No             |
| Temperature Range - Operating  | -40° to +105°C |
| Termination Interface Style    | Through Hole   |

# Mates With / Use With

# Mates with Part(s)

| Description                           | Part Number |
|---------------------------------------|-------------|
| iGrid Dual Row Receptacle<br>Housings | 501646      |