

Data sheet

SP044xxVBNN ASP044

Page 1/5

P/N

ASP044xx22

xx=number of poles


2024/05/23

Version: S

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- spring clamp terminal block, pluggable
- centerline 3.81 mm, direction of connection vertical 0°
- color black
- eccentric lever, wire entry uncodeable side parallel to plug direction



U | Contact

Data sheet
SP044xxVBNN ASP044

Page 2/5

P/N
ASP044xx22
xx=number of poles
2024/05/23
Version: S

Technical Data

General Data			
min. number of poles	2		
max. number of poles	12		
Insulating material class	CTI 400		
clearance/creepage dist.	2.6 mm		
Protection category	IP20		
Min. insul. strip length	6 mm		
Rated current	10 A		
Overvoltage category	III	III	II
Pollution degree	2	2	2
Rated voltage	32 V	200 V	200 V
Rated test voltage	1.5 kV	1.5 kV	1.5 kV
Terminal data			
rat.wiring solid AWGmax	0.08 mm² - 1.5 mm² / AWG 28 - AWG 16		
rat.wiring strand.AWGmax	0.08 mm² - 1.5 mm² / AWG 28 - AWG 16		
Approvals			
 V / A	150 / 10		
approval UL - File No.	E121004		
 1.5 mm²	130 V / 2.5 kV / 10 A		
Material			
insulating material	PA46		
flammability class	V0		
spring material	Spring steel		
contact material	CuSn		
Contact surface	Sn		
Glow-Wire Flammability GWFI	-		
Glow-Wire Flammability GWIT	-		
Climatic Data			
upper limit temperature	105 °C		
lower limit temperature	-40 °C		
general			

U | Contact

Data sheet

SP044xxVBNN ASP044

Page 3/5

P/N

ASP044xx22

xx=number of poles

2024/05/23

Version: S

Technical Data

Tolerance

ISO 2768 -mH



U | Contact

Data sheet

Page 4/5

SP044xxVBNN ASP044

P/N

ASP044xx22**xx=number of poles**

2024/05/23

Version: S

Counterpart

P/N	Designation
311901	PR044xxHBBN Type 190
311911	PR044xxVBNN Type 191
313821	PT094xxHBBN Type 382
313831	PT094xxVBNN Type 383

U | Contact

Data sheet

SP044xxVBNN ASP044

Page 5/5

P/N

ASP044xx22


xx=number of poles

2024/05/23

Version: S

Illustrations

Dimensional drawing



$L = (\text{pole size} - 1) \times \text{centerline} + 4 \text{ mm} [0.157]$