

#### Buchanan

TE Internal #: 2350398-5

PCB Terminal Blocks, Plug, Wire-to-Board, 5 Position, .137 in [3.5 mm] Centerline, 1 Row, 180° Wire Entry Angle, 24 – 16 AWG Wire

Size


View on TE.com >





Connectors > Terminal Blocks & Strips > PCB Terminal Blocks











Terminal Block Connector Type: Plug

Connector System: Wire-to-Board

Number of Positions: 5

Centerline (Pitch): 3.5 mm [ .137 in ]

Terminal Block Connector Type

Number of Rows: 1

#### **Features**

## **Product Type Features**

| Connector System                  | Wire-to-Board  |
|-----------------------------------|----------------|
| Connector & Contact Terminates To | Wire & Cable   |
| Configuration Features            |                |
| Wire Entry Location               | Тор            |
| Stacking Configuration            | Side Stackable |
| Number of Positions               | 5              |
| Number of Rows                    | 1              |
| Wire Entry Angle                  | 180°           |
| Electrical Characteristics        |                |
| Operating Voltage                 | 150 VAC        |

Plug

| Primary Product Color | Green    |
|-----------------------|----------|
| Product Orientation   | Vertical |



#### **Contact Features**

| Contact Mating Area Plating Material | Tin             |
|--------------------------------------|-----------------|
| Contact Base Material                | Phosphor Bronze |
| Contact Current Rating (Max)         | 8 A             |

| Contact Current Rating (Max)       | 8 A                        |
|------------------------------------|----------------------------|
| Termination Features               |                            |
| Termination Method to Wire & Cable | Push-in, Spring Terminal   |
| Housing Features                   |                            |
| Housing Material                   | PA 66                      |
| Centerline (Pitch)                 | 3.5 mm[.137 in]            |
| Dimensions                         |                            |
| Wire Size                          | .05 – 1.31 mm²             |
| Usage Conditions                   |                            |
| Operating Temperature Range        | -40 - 105 °C[-40 - 221 °F] |
| Operation/Application              |                            |
| Circuit Application                | Signal                     |
| Packaging Features                 |                            |

Box

**Product Compliance** 

Packaging Method

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                               |
| Solder Process Capability                     | Not reviewed for solder process capability  |

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# **Customers Also Bought**























#### **Documents**

## **Product Drawings**

5 POS SPRING TB PLUG , PITCH 3.50

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2350398-5\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2350398-5\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2350398-5\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

**BUCHANAN PUSH-IN CLAMP PCB CONNECTORS** 

English

# **Product Specifications**

**Application Specification** 

English

## Agency Approvals

UL

English