

**SV 7.62HP/08/90MSF5 3.5SN BK BX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

Single-row, high-current and high-performance male headers for side-by-side mounting without sacrificing any poles or with flange for fast fixing without tools. Maximum connection and operating reliability thanks to a mating profile that prevents incorrect connection, unique coding diversity and additional fastening in the flange.

**General ordering data**

|              |                                                                                                                                                                                   |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version      | PCB plug-in connector, male header, closed side, Middle screw flange, THT solder connection, 7.62 mm, Number of poles: 8, 180°, Solder pin length (l): 3.5 mm, tinned, black, Box |
| Order No.    | <a href="#">2474130000</a>                                                                                                                                                        |
| Type         | SV 7.62HP/08/90MSF5 3.5SN BK BX                                                                                                                                                   |
| GTIN (EAN)   | 4050118485929                                                                                                                                                                     |
| Qty.         | 24 pc(s).                                                                                                                                                                         |
| Product data | IEC: 1000 V / 57 A<br>UL: 300 V / 40.5 A                                                                                                                                          |
| Packaging    | Box                                                                                                                                                                               |

Creation date June 5, 2024 9:41:04 AM CEST

## SV 7.62HP/08/90MSF5 3.5SN BK BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 11.4 mm  | Depth (inches)  | 0.449 inch |
| Height     | 28.3 mm  | Height (inches) | 1.114 inch |
| Width      | 68.58 mm | Width (inches)  | 2.7 inch   |
| Net weight | 15.504 g |                 |            |

## System specifications

|                                              |                                            |                   |                                           |
|----------------------------------------------|--------------------------------------------|-------------------|-------------------------------------------|
| Product family                               | OMNIMATE Power - series BV/SV 7.62HP       |                   |                                           |
| Type of connection                           | Board connection                           |                   |                                           |
| Mounting onto the PCB                        | THT solder connection                      |                   |                                           |
| Pitch in mm (P)                              | 7.62 mm                                    |                   |                                           |
| Pitch in inches (P)                          | 0.3 "                                      |                   |                                           |
| Outgoing elbow                               | 180°                                       |                   |                                           |
| Number of poles                              | 8                                          |                   |                                           |
| Number of solder pins per pole               | 2                                          |                   |                                           |
| Solder pin length (l)                        | 3.5 mm                                     |                   |                                           |
| Solder pin length tolerance                  | +0.1 / -0.3 mm                             |                   |                                           |
| Solder pin dimensions                        | 0.8 x 1.0 mm                               |                   |                                           |
| Solder eyelet hole diameter (D)              | 1.4 mm                                     |                   |                                           |
| Solder eyelet hole diameter tolerance (D)    | + 0,1 mm                                   |                   |                                           |
| L1 in mm                                     | 53.34 mm                                   |                   |                                           |
| L1 in inches                                 | 2.1 "                                      |                   |                                           |
| Number of rows                               | 1                                          |                   |                                           |
| Pin series quantity                          | 1                                          |                   |                                           |
| Touch-safe protection acc. to DIN VDE 57 106 | Touch-safe above the printed circuit board |                   |                                           |
| Touch-safe protection acc. to DIN VDE 0470   | IP 20                                      |                   |                                           |
| Protection degree                            | IP20, when fully mounted                   |                   |                                           |
| Volume resistance                            | 2.00 mΩ                                    |                   |                                           |
| Can be coded                                 | Yes                                        |                   |                                           |
| Tightening torque for screw flange, min.     | 0.2 Nm                                     |                   |                                           |
| Tightening torque for screw flange, max.     | 0.3 Nm                                     |                   |                                           |
| Plugging cycles                              | 25                                         |                   |                                           |
| Tightening torque                            | Torque type                                | Screw flange      |                                           |
|                                              | Usage information                          | Thickness         | nominal 1.6 mm                            |
|                                              |                                            |                   | nominal 3.2 mm                            |
|                                              |                                            | Tightening torque | min. 0.65 Nm                              |
|                                              |                                            |                   | max. 0.85 Nm                              |
|                                              |                                            | Recommended screw | Part number                               |
|                                              |                                            |                   | Screw type EJOT Delta PT 30x10 or similar |
|                                              |                                            | Thickness         | nominal 4.8 mm                            |
|                                              |                                            |                   | min. 0.8 Nm                               |
|                                              |                                            | Tightening torque | max. 1 Nm                                 |
|                                              |                                            |                   | Recommended screw                         |
|                                              |                                            | Part number       |                                           |
|                                              |                                            |                   | Screw type EJOT Delta PT 30x12 or similar |

## SV 7.62HP/08/90MSF5 3.5SN BK BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Material data

|                                       |                                |                                       |                                |
|---------------------------------------|--------------------------------|---------------------------------------|--------------------------------|
| Insulating material                   | PA GF                          | Colour                                | black                          |
| Colour chart (similar)                | RAL 9011                       | Insulating material group             | II                             |
| Comparative Tracking Index (CTI)      | ≥ 500                          | UL 94 flammability rating             | V-0                            |
| Contact material                      | Copper alloy                   | Contact surface                       | tinned                         |
| Layer structure of solder connection  | 1...3 µm Ni / 4...6 µm Sn matt | Layer structure of plug contact       | 1...3 µm Ni / 4...6 µm Sn matt |
| Storage temperature, min.             | -40 °C                         | Storage temperature, max.             | 70 °C                          |
| Operating temperature, min.           | -50 °C                         | Operating temperature, max.           | 130 °C                         |
| Temperature range, installation, min. | -25 °C                         | Temperature range, installation, max. | 130 °C                         |

## Rated data acc. to IEC

|                                                                           |                        |                                                                       |                   |
|---------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------|-------------------|
| tested acc. to standard                                                   | IEC 60664-1, IEC 61984 | Rated current, min. number of poles (Tu=20°C)                         | 57 A              |
| Rated current, max. number of poles (Tu=20°C)                             | 41 A                   | Rated current, min. number of poles (Tu=40°C)                         | 41 A              |
| Rated current, max. number of poles (Tu=40°C)                             | 41 A                   | Rated voltage for surge voltage class / pollution degree II/2         | 1,000 V           |
| Rated voltage for surge voltage class / pollution degree III/2            | 630 V                  | Rated voltage for surge voltage class / pollution degree III/3        | 630 V             |
| Rated impulse voltage for surge voltage class/ pollution degree II/2      | 6 kV                   | Rated impulse voltage for surge voltage class/ pollution degree III/2 | 6 kV              |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 6 kV                   | Short-time withstand current resistance                               | 3 x 1s with 420 A |
| Clearance, min.                                                           | 6.9 mm                 | Creepage distance, min.                                               | 9.6 mm            |

## Rated data acc. to CSA

|                                   |       |                                   |       |
|-----------------------------------|-------|-----------------------------------|-------|
| Rated voltage (Use group B / CSA) | 300 V | Rated voltage (Use group C / CSA) | 300 V |
| Rated voltage (Use group D / CSA) | 600 V | Rated current (Use group B / CSA) | 35 A  |
| Rated current (Use group C / CSA) | 35 A  | Rated current (Use group D / CSA) | 5 A   |

## Rated data acc. to UL 1059

|                                       |        |                                       |        |
|---------------------------------------|--------|---------------------------------------|--------|
| Rated voltage (Use group B / UL 1059) | 300 V  | Rated voltage (Use group C / UL 1059) | 300 V  |
| Rated voltage (Use group D / UL 1059) | 600 V  | Rated voltage (Use group F / UL 1059) | 744 V  |
| Rated current (Use group B / UL 1059) | 40.5 A | Rated current (Use group C / UL 1059) | 40.5 A |
| Rated current (Use group D / UL 1059) | 5 A    | Rated current (Use group F / UL 1059) | 40.5 A |
| Clearance distance, min.              | 6.9 mm | Creepage distance, min.               | 9.6 mm |

## Packing

|           |        |            |        |
|-----------|--------|------------|--------|
| Packaging | Box    | VPE length | 351 mm |
| VPE width | 135 mm | VPE height | 40 mm  |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002637    | ETIM 7.0    | EC002637    |
| ETIM 8.0    | EC002637    | ETIM 9.0    | EC002637    |
| ECLASS 9.0  | 27-44-04-02 | ECLASS 9.1  | 27-44-04-02 |
| ECLASS 10.0 | 27-44-04-02 | ECLASS 11.0 | 27-46-02-01 |
| ECLASS 12.0 | 27-46-02-01 | ECLASS 13.0 | 27-46-02-01 |

**SV 7.62HP/08/90MSF5 3.5SN BK BX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Important note**

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.                                                                                                                                                                                                                                                                                                                                                                                                 |
| Notes          | <ul style="list-style-type: none"><li>• Additional variants on request</li><li>• Rated current related to rated cross-section &amp; min. No. of poles.</li><li>• P on drawing = pitch</li><li>• Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.</li><li>• In accordance with IEC 61984, OMNIMATE-connectors are connectors without breaking capacity (COC). During designated use, connectors are not allowed to be engaged or disengaged when live or under load</li><li>• Long term storage of the product with average temperature of 50 °C and maximum humidity 70%, 36 months</li></ul> |




**Downloads**

|                  |                                                              |
|------------------|--------------------------------------------------------------|
| Engineering Data | <a href="#">CAD data – STEP</a>                              |
| Catalogues       | <a href="#">Catalogues in PDF-format</a>                     |
| Brochures        | <a href="#">FL DRIVES EN</a><br><a href="#">FL DRIVES DE</a> |

**SV 7.62HP/08/90MSF5 3.5SN BK BX**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings****Product image****Dimensional drawing****Dimensional drawing**

## Recommended wave soldering profiles

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

### Single Wave:



### Double Wave:



### Wave soldering profiles

Wired connection elements should be processed in accordance with the DIN EN 61760-1 standard. We have included two recommendations for practical wave soldering profiles, with which Weidmüller PCB terminals and connectors are qualified.

When choosing a suitable profile for your application, the following factors also need to be considered:

- PCB thickness
- Proportion of Cu in the layers
- Single/double-sided assembly
- Product range
- Heating and cooling rates

The single and double wave profiles each indicate the recommended operating range, including the maximum soldering temperature of 260°C. In practice, the maximum soldering temperature is quite often well below the above maximum profile.

We reserve the right to make technical changes.